

Product: <u>734D1</u> ☑

DS-3 and DS-4, 734D Series, #20-1 SPC Coax, CMR/CMG



Product Description

20 AWG solid .032" (.81mm) silver-plated copper conductor(s), gas-injected FHDPE insulation, Beldfoil®; tinned copper braid shield (85% coverage), overall PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

| AWG | Stranding | Material | Nominal Diameter | No. of Coax |
|------------------|-----------|-------------------------------------|------------------|-------------|
| 20 | Solid | SCCS - Silvered Copper Covered Stee | l 0.032 in | 1 |
| Conductor Count: | | 1 | | |
| nsulatio | on | | | |
| | Material | Nominal Diameter | | |
| | | Ecom) 0.149 in | | |

Outer Shield Material

| Туре | Layer | Material | Material Trade Name | Coverage [%] |
|-------|-------|-------------------------|---------------------|--------------|
| Таре | 1 | Bi-Laminate (Alum+Poly) | Beldfoil® | 100% |
| Braid | 2 | Tinned Copper (TC) | | 85% |

Outer Jacket Material

| Material | Nominal Diameter |
|--------------------------|------------------|
| PVC - Polyvinyl Chloride | 0.235 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Conductor DCR Conductor Resistance | Nominal Outer Shield DCR | Outer Conductor DCR |
|--------------------------|--|--------------------------|---------------------|
| 10 Ohm/1000ft | 10 Ohm/1000ft | 2.4 Ohm/1000ft | 2.4 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Shield |
|--------------------------------------|
| 16.8 pF/ft |

Inductance

Nominal Inductance 0.097 µH/ft

Impedance

Nominal Characteristic Impedance 75 Ohm

Return Loss (RL)

Frequency [MHz] Minimum Return (RL)

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|--|
| 1.27 ns/ft | 80% |

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

| Operating Temp Range: | -40°C To +75°C |
|-----------------------|----------------|
| | |

Mechanical Characteristics

| Bulk Cable Weight: | 31 lbs/1000ft |
|-----------------------------|---------------|
| Max. Pull Tension: | 60 lbs |
| Min Bend Radius/Minor Axis: | 2.5 in |

Standards

| NEC/(UL) Compliance: | CMR |
|-----------------------|-------------------------------------|
| CEC/C(UL) Compliance: | CMG |
| RG Type: | 59/U Type |
| Other Compliance: | Telcordia Specification GR-139-CORE |

Applicable Environmental and Other Programs

| Environmental Space: | Indoor - Riser |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | No |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01 |
| MII Order #39 (China RoHS): | Yes |

Suitability

| Suitability - Burial: | No |
|-----------------------|-----|
| Suitability - Indoor: | Yes |

Flammability, LS0H, Toxicity Testing

| UL Flammability: | UL1666 Vertical Shaft |
|--------------------|-----------------------|
| CSA Flammability: | FT4 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| Plenum (Y/N): | No |
|----------------|--------|
| Plenum Number: | 734D1P |

Part Number

| ltem # | Color | Putup Type | Length | UPC |
|---------------|-------|------------|----------|-------------|
| 734D1 008500 | Gray | Reel | 500 ft | 61282518444 |
| 734D1 0081000 | Gray | Reel | 1,000 ft | 61282518439 |
| Footnote: | | | | |

Update and Revision:

Revision Number: 0.278 Revision Date: 09-30-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.