



Product: [3087A](#)

DeviceBus® for Honeywell SDS, 2 Pr #22 Str TC, PVC+FPE Ins, IS, PVC Jkt, CL2

[Request Sample](#)

Product Description

DeviceBus® for Honeywell SDS, 2 Pair 22AWG (19x34) Tinned Copper, PVC+Foam PE Insulation, Individual Beldfoil® Shield, PVC Outer Jacket, CL2

Technical Specifications

Suitable Applications:	harsh environment, IIoT, factory or process automation, video, audio, data communication, etc.
------------------------	--

Conductor

Element	Number of Element	AWG	Stranding	Material
Power Pair(s)	1	22	19x34	TC - Tinned Copper
Data Pair(s)		22	19x34	TC - Tinned Copper

Insulation

Element	Material	Thickness	Color Code
Power Pair(s)	PVC - Polyvinyl Chloride	0.010 in	Blue & Brown
Data Pair(s)	PE - Polyethylene (Foam)	0.034 in	Black & White

Inner Shield Material

Element	Shield Type	Material	Coverage	Drainwire Type	Notes
Power Pair(s)	Tape	Bi-Laminate (Alum+Poly)	100%		
Data Pair(s)	Tape	Bi-Laminate (Alum+Poly)	100%	22 AWG (19x34) TC	Power & Data Pairs share same Drainwire

Outer Jacket Material

Material	Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.035 in	0.290 in

Cable Diameter (Nominal):	0.290 in
---------------------------	----------

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Characteristic Impedance	Nom. Velocity of Prop.	Max. Current
Power Pair(s)	17.5 Ohm/1000ft				3 Amps per Conductor at 25°C
Data Pair(s)	17.5 Ohm/1000ft	12 pF/ft	120 Ohm	76%	

Nom Outer Shield DCR:	7.9 Ohm/1000ft
-----------------------	----------------

High Frequency (Nominal/Typical)

Element	Frequency [MHz]	Nom. Insertion Loss
Data Pair(s)	0.125 MHz	0.23 dB/100ft
	0.5 MHz	0.42 dB/100ft
	1.0 MHz	0.6 dB/100ft

High Freq

Max./Min. Input Impedance (unFitted)
120 Ohm

Voltage

UL Voltage Rating
300 V (UL AWM 2464)

Temperature

UL Rating	Operating	Storage
80°C	-30°C to +80°C	-40°C to +80 °C

Bend Radius

Stationary Min.	Installation Min.
2.9 in	6 in

Max. Pull Tension:	47.5 lbs
Bulk Cable Weight:	33 lbs/1000ft
Environmental Suitability:	Indoor
Flammability / Fire Resistance:	UL1685 UL Loading, FT1
NEC / UL Compliance:	Article 725, CL2
AWM Compliance:	2464, I/II A
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Notes:	Micro Cable (Drop)
Update and Revision:	Revision Number: 0.354 Revision Date: 09-30-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.