



Product: [3078F](#)

Fieldbus, 1 Pr #22 Str TC, FPE Ins, OS, PVC Jkt, Flexible High Speed, CM, PLTC

Request Sample

Product Description

Fieldbus, 1 Pair 22AWG (7x30) Tinned Copper, Foam PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, Flexible High Speed, CM, PLTC

Technical Specifications

Suitable Applications:	harsh environment digital and serial two-way communication, oil and gas extraction and refining sites, petrochemical, Profibus process automation or Foundation FieldBus process automation, extreme temperature environments, exposure to humidity/moisture, dust, and oil, remote locations long distance applications, etc.
------------------------	--

Conductor

Element	Number of Element	AWG	Stranding	Material
Pair(s)	1	22	7x30	TC - Tinned Copper

Insulation

Element	Material	Thickness	Color Code	Notes
Pair(s)	PE - Polyethylene (Foam)	0.046 in	Blue & Orange	HDPE w/ Skin

Outer Shield Material

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	20 AWG (7x28) TC

Outer Jacket Material

Material	Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.050 in	0.351 in

Cable Diameter (Nominal):	0.351 in
---------------------------	----------

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Shield	Max. Capacitance Unbalance	Characteristic Impedence	Nom. Velocity of Prop.	Max. Current
Pair(s)	17.1 Ohm/1000ft	16 pF/ft	0.46 pF/ft	150 Ohm	78%	2.5 Amps per Conductor

High Frequency (Nominal/Typical)

Element	Frequency [MHz]	Nom. Insertion Loss
Pair(s)	0.25 MHz	0.18 dB/100ft
	0.625 MHz	0.26 dB/100ft
	1.25 MHz	0.34 dB/100ft
	3.125 MHz	0.55 dB/100ft

High Freq

Max./Min. Input Impedance (unFitted)
150 Ohm

Voltage

UL Voltage Rating
300 V (CM, PLTC)

Temperature

UL Rating	Operating
75°C	-40°C to +75°C

Bend Radius

Stationary Min.
3.5 in

Max. Pull Tension:	32 lbs
Bulk Cable Weight:	40 lbs/1000ft
Environmental Suitability:	Sunlight Resistance
Flammability / Fire Resistance:	UL1685 UL Loading
NEC / UL Compliance:	Article 725, Article 800, CM, PLTC
CEC / C(UL) Compliance:	CM
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Notes:	CPE & LSzH Jacket optional
Update and Revision:	Revision Number: 0.380 Revision Date: 09-30-2020

© 2020 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.