


Product: [7784ENH](#) 

VIDEO TRIAX 11 FRNC/LSZH



Product Description

VIDEO TRIAX 11 FRNC/LSZH

Technical Specifications

Product Overview

Suitable Applications:	Triaxial camera cable
------------------------	-----------------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
15	Solid	BC - Bare Copper	1.4 mm	1

Conductor Count:	1
------------------	---

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene (Foam)	6.5 mm	0.2 mm

Inner Shield Material

Type	Material	Coverage [%]	Nominal Diameter
Braid	Bare Copper (BC)	80%	7.2 mm

Inner Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PE - Polyethylene	8.5 mm	0.2 mm

Outer Shield Material

Type	Material	Nominal Diameter	Min. Coverage [%]
Braid	Bare Copper (BC)	9.1 mm	80%

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
LSZH - Low Smoke Zero Halogen (Flame Retardant)	11 mm	0.2 mm

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Inner Shield DCR	Nominal Outer Shield DCR
11.2 Ohm/km	6.5 Ohm/km	7 Ohm/km

Capacitance

Nom. Capacitance Conductor to Shield
55 pF/m

Inductance

Nominal Inductance0.4 μ H/m**Impedance****Nominal Characteristic Impedance**

75 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.5 dB/100m
3.58 MHz	1 dB/100m
5 MHz	1.2 dB/100m
7 MHz	1.3 dB/100m
10 MHz	1.6 dB/100m
67.5 MHz	4.1 dB/100m
71.5 MHz	4.3 dB/100m
88.5 MHz	4.8 dB/100m
100 MHz	5.2 dB/100m
135 MHz	6 dB/100m
143 MHz	6.2 dB/100m
180 MHz	7.1 dB/100m
270 MHz	8.7 dB/100m
300 MHz	9 dB/100m
360 MHz	10.2 dB/100m
540 MHz	12.8 dB/100m
720 MHz	15 dB/100m
750 MHz	15.4 dB/100m
1000 MHz	18.2 dB/100m
1500 MHz	23 dB/100m
2000 MHz	27.4 dB/100m
2250 MHz	29.4 dB/100m
3000 MHz	35.1 dB/100m

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
410 ns/ft	81%

High Freq

Frequency [MHz]	Min. SRL (Structural Return Loss)
5 - 850 MHz	23 dB

Screening

Frequency [MHz]	Min. Screening Attenuation
30 - 850 MHz	75 dB

Voltage**Voltage Rating [V]**

400 V RMS

Table Notes: Maximum operating

Temperature Range

Installation Temp Range:	-5°C To +70°C
Storage Temp Range:	-30°C To +70°C
Operating Temp Range:	-30°C To +70°C

Mechanical Characteristics

Max. Pull Tension:	300 N
Min Bend Radius (W/o Pulling Strength):	110 mm

Standards

Series Type:	Triax 8/11/14
--------------	---------------

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU RoHS Compliance Date (yyyy-mm-dd):	2016-05-20

Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
IEC 60754-1 (EN50267-1)- Halogen Amount:	Zero

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
7784ENH.02500	Red	Reel	500 m	8719605014498
7784ENH.021000	Red	Reel	1,000 m	8719605014481

History

Update and Revision:	Revision Number: 0.183 Revision Date: 09-30-2020
----------------------	--------------------------------------------------

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.