



Product: 70063CH ☑

1 x QUAD SNAKE, 26AWG, LSZH-C

Product Description

AUDIO 1 x QUAD SNAKE, 26AWG/0.14mm², LSZH-C

Technical Specifications

Product Overview

Suitable Applications:	Single star-quad FRNC/LSZH microphone cable

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Quads
26	19x34	BC - Bare Copper	1
Condu	uctor Count:		
Total N	Total Number of Pairs:		

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance	
PE - Polyethylene	1.15 mm	0.05 mm	

Color Chart

Number	Color		
Quad 1	White & Blue & White/Blue & Blue/White		
Table Notes:		With ringmarking	\neg

Outer Shield Material

Туре	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D	Drainwire Position
Таре	Bi-Laminate (Alum+Poly)	100%	TC - Tinned Copper	26	Stranded	Under shielding foil

Outer Jacket Material

Material	Nominal Diameter	
LSZH - Low Smoke Zero Halogen (Flame Retardant)	4.7 mm	

Construction and Dimensions

Cabling

Description
1 quad + drainwire stranded tinnend copper (AWG26)(7x0.16mm) + Strength member

Strength Member



Electrical Characteristics



Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Shield
164 pF/m	164 pF/m

Temperature Range

Other Temp Range:	-30-+70 °C
-------------------	------------

Standards

CPR Euroclass:	Eca	

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Eca
EU RoHS Compliance Date (yyyy-mm-dd):	2016-04-14

Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2 and IEC 60332-3-24	
-------------------	----------------------------------	--

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
70063CH.00100	Black	Reel	100 m	8719605142290
70063CH.00500	Black	Reel	500 m	8719605010544

History

Update and Revision:	Revision Number: 0.104 Revision Date: 09-30-2020				

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.