



Product: [PRG11A2](#)

COAX PRG11 AL PVC CATV

Product Description

COAX [1.55/7.25] PRG11 AL PVC CATV

Technical Specifications

Product Overview

Suitable Applications:	Coaxial cables used in cabled distribution networks designed according the European Standard EN 50117; Operating at frequencies between 5 MHz and 2150 MHz; The International Standard IEC 1196
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
15	Solid	BC - Bare Copper	1.55 mm	0.02 mm	1

Conductor Count: 1

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene (Foam)	7.25 mm	0.2 mm

Table Notes: Centricity min. 85%

Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Tri-Laminate (Alum+Poly+Alum)	100%	2 mm			
Braid	2	Tinned Copper (TC)	45%		7.9 mm	0.25 mm	5%

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	10.1 mm	0.3 mm

Table Notes: According to European Standard EN 50290-2-20

Construction and Dimensions

Min Elongation at Breakof Jacket:	150 %
Min Tensile Strength of Jacket:	12.5 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
9.4 Ohm/km	22.2 Ohm/1000ft	12.8 Ohm/km

Capacitance

Nom. Capacitance	Capacitance Tolerance
55 pF/m	2 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance

75 Ohm	3 Ohm	Min. 46 dB
--------	-------	------------

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	0.9 dB/100m
50 MHz	2.9 dB/100m
100 MHz	4.1 dB/100m
200 MHz	5.9 dB/100m
400 MHz	8.6 dB/100m
600 MHz	10.7 dB/100m
800 MHz	12.5 dB/100m
1000 MHz	14.2 dB/100m
1350 MHz	16.8 dB/100m
1600 MHz	18.5 dB/100m
1750 MHz	19.5 dB/100m
2150 MHz	21.9 dB/100m
2400 MHz	23.4 dB/100m
3000 MHz	26.7 dB/100m

Table Notes: Max. attenuation 10% higher

Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
81%	2%

High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 30 MHz	26 dB
30 - 470 MHz	26 dB
470 - 1000 MHz	23 dB
1000 - 2000 MHz	18 dB
2000 - 3000 MHz	16 dB

Table Notes: In each frequency band, 3 peak values up to 4 dB lower are allowed

Screening

Frequency [MHz]	Min. Screening Attenuation
30 - 1000 MHz	85 dB

Voltage

Voltage Test Dielectric
3.0 kV DC

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-15°C To +70°C
Operating Temp Range:	-15°C To +70°C

Mechanical Characteristics

Bulk Cable Weight:	95 kg/km
Min Bend Radius (W/o Pulling Strength):	50 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	12-120 N at 25 mm N

Standards

IEC Compliance:	IEC 1196
CPR Euroclass:	Eca
CENELEC Compliance:	EN 50117 and EN 50117-1
RG Type:	11/U Type

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Eca
----------------------	------------------------

EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01
---------------------------------------	------------

Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
-------------------	---------------

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
PRG11A2.00250	White	Reel	250 m	8719605105806
PRG11A2.00500	White	Reel	500 m	8719605105813

History

Update and Revision:	Revision Number: 0.181 Revision Date: 12-17-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.