



Product: [1624P](#) 

Category 5 Cable, 4 Pair, F/UTP, CMP

Product Description

Category 5 Premise Horizontal Cable (100MHz), 4 Pair, 24 AWG Solid Bare Copper Conductors, F/UTP - Foil Shielded, Plenum-CMP, Flamarrest® PVC-LS Jacket

Technical Specifications

Product Overview

Suitable Applications:	Premise Horizontal Cable, Ethernet 1000BASE-T, Ethernet 100BASE-TX, Ethernet 10BASE-T, PoE++, PoE+, PoE , Noisy Environments
------------------------	--

Construction Details

Conductor

AWG	Stranding	Material	Number of Pairs
24	Solid	BC - Bare Copper	4

Insulation

Material	Thickness	Color Code
FEP - Fluorinated Ethylene Propylene	0.01 in	White/Blue Bandmark & Blue, White/Orange Bandmark & Orange, White/Green Bandmark & Green, White/Brown Bandmark & Brown

Bonded-Pair:	No
--------------	----

Outer Shield Material

Type	Material	Coverage	Drainwire Type
Tape	Polyester + Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC

Outer Jacket Material

Material	Material Trade Name	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	Flamarrest®	0.235 in	No

Electrical Characteristics

Electricals

Max. Conductor DCR	Max. DCR Unbalance	Nom. Mutual Capacitance
93.8 Ohm/km	3%	15 pF/ft

Delay

Max. Delay	Max. Delay Skew	Nom. Velocity of Propagation (VP) [%]
538 ns/100m	45 ns/100m	67%

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. SRL (Structural Return Loss)	Max./Min. Fitted Impedance
1 MHz	2 dB/100m	62.2 dB	62.3 dB	23 dB	100 ± 15 Ohm
4 MHz	4.1 dB/100m	53.3 dB	53.3 dB	23 dB	100 ± 15 Ohm
8 MHz	5.8 dB/100m	48.8 dB	48.8 dB	23 dB	100 ± 15 Ohm
10 MHz	6.5 dB/100m	47.3 dB	47.3 dB	23 dB	100 ± 15 Ohm
16 MHz	8.2 dB/100m	44.3 dB	44.3 dB	23 dB	100 ± 15 Ohm
20 MHz	9.3 dB/100m	42.8 dB	42.8 dB	23 dB	100 ± 15 Ohm
25 MHz	10.4 dB/100m	41.3 dB	41.3 dB	22 dB	100 ± 15 Ohm

31.25 MHz	11.7 dB/100m	39.9 dB	39.9 dB	21.1 dB	100 ± 15 Ohm
62.5 MHz	17 dB/100m	35.4 dB	35.4 dB	18 dB	100 ± 15 Ohm
100 MHz	22 dB/100m	32.2 dB	32.3 dB	16 dB	100 ± 15 Ohm

Voltage

UL Voltage Rating
300 V (CMP)

Mechanical Characteristics

Temperature

Operating
-20°C To +75°C

Bend Radius

Stationary Min.	Installation Min.
1 in	2.35 in

Max. Pull Tension:	25 lbs
Bulk Cable Weight:	34 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Plenum, Indoor
Flammability / Fire Resistance:	NFPA 262, UL 910 (Plenum), FT6, FT6, IEC 60332-1-2
NEC / UL Compliance:	800, CMP
CEC / C(UL) Compliance:	CMP
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3
Data Category:	Category 5
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Part Number

Non-Plenum Number:	1624R
--------------------	-------

Variants

Item #	Color	Putup Type	Length	UPC
1624P D151000	Blue	Reel	1,000 ft	612825119371
1624P D15A1000	Blue	Reel-in-Box	1,000 ft	612825119364
1624P 0081000	Gray	Reel	1,000 ft	612825119456
1624P 008A1000	Gray	Reel-in-Box	1,000 ft	612825119449
1624P 0051000	Green	Reel	1,000 ft	612825119425
1624P 8771000	Natural	Reel	1,000 ft	612825119470
1624P 877A1000	Natural	Reel-in-Box	1,000 ft	612825119463
1624P 0031000	Orange	Reel	1,000 ft	612825119395
1624P 0071000	Purple	Reel	1,000 ft	612825119432
1624P 0021000	Red	Reel	1,000 ft	612825119388
1624P 0041000	Yellow	Reel	1,000 ft	612825119418
1624P 004A1000	Yellow	Reel-in-Box	1,000 ft	612825119401

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. RJ-45 Compatible. Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5.
--------	--

History

Update and Revision:	Revision Number: 0.269 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.