

**Product:** <u>70066</u> ☑





# 8 x QUAD SNAKE, 26AWG, PVC

# **Product Description**

AUDIO 8 x QUAD SNAKE, 26AWG/0.14mm², PVC

# **Technical Specifications**

# **Product Overview**

Suitable Applications:	8 fold star-quad microphone cable

# **Physical Characteristics (Overall)**

### Conductor

AWG	Stranding	Material	Construction n x D
26	Stranded	ed BC - Bare Copper 19x0.10 mm	
Condu	uctor Count:		

### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Insulatio	n PE - Polyethylene	1.15 mm	0.05 mm

# **Color Chart**

Quad 1	White & Blue & White/Blue & Blue/White
Quau i	White & Dide & White/Dide & Dide/White
_	
Table Notes:	

# Color Chart 2

Number	Color
Quad 1	1
Quad 2	2
Quad 3	3
Quad 4	4
Quad 5	5
Quad 6	6
Quad 7	7
Quad 8	8

## Inner Shield Material

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D	Drainwire Position
Таре	Bi-Laminate (Alum+Poly)	100%	Stranded tinned copper	26	7x0.16 mm	Under shielding foil
Table Notes:		Alumii	Aluminum inside			

# Inner Jacket Material

## Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
PVC - Polyvinyl Chloride	16.70 mm	0.50 mm	1.50 mm

### **Construction and Dimensions**

#### Cabling

Description
1 center filler + 8 quads + 7 fillers + 1 stranded tinned copper drainwire (16AWG) (26x0.254 mm) covered with a non-woven foil

### **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR 110.0 Ohm/km

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Shield
164 pF/m	222 pF/m

### Voltage

Voltage Rating [V] 300 V

### **Temperature Range**

Other Temp Range:	-30 to +70 °C	

### **Mechanical Characteristics**

Min Bend Radius During Installation:	167 mm
Min Bend Radius During Operation:	250.5 mm

# **Applicable Environmental and Other Programs**

Environmental Space:	Indoor
EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01

# **Part Number**

### Variants

	Item #	Color	Putup Type	Length	EAN
ľ	70066.00500	Black	Reel	500 m	8719605010599

# History

Update and Revision:	Revision Number: 0.140 Revision Date: 08-25-2020			

### © 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.