



# Product: <u>9228</u> ☑

 $93\Omega$  RG-62A/U Type, #22 Sol BCCS, Semi-solid PE, BC Braid, HDPE Jkt, Burial

# **Product Description**

Coax 93Ω RG-62A/U Type, 22 AWG solid bare copper-covered steel, semi-solid polyethylene insulation, bare copper braid shield (95% coverage), high-density polyethylene jacket, Burial

# **Technical Specifications**

### **Product Overview** Suitable Applications: Computer, Instrumentation **Construction Details** RG Type: 62 Conductor AWG Stranding Nom. Diameter Material BCCS - Bare Copper Covered Steel 22 Solid 0.025 in Insulation Material Nom. Diameter Notes PE - Polyethylene (Semi-Solid) 0.146 in Solid PE monofilament spiral around conductor. Solid PE tube over monofilament Outer Shield Material Outer Shield Type Material Layer Coverage Braid Bare Copper (BC) 95% 1 **Outer Jacket Material** Material Nom. Diameter PE - Polyethylene 0.242 in Table Notes: Flooding grease under jacket **Electrical Characteristics**

## Attenuation

Frequency	Nom. Attenuation [dB/100ft]
1 MHz	0.30 dB/100ft
10 MHz	0.90 dB/100ft
50 MHz	1.90 dB/100ft
100 MHz	2.70 dB/100ft
200 MHz	3.80 dB/100ft
400 MHz	5.30 dB/100ft
700 MHz	7.30 dB/100ft
900 MHz	8.20 dB/100ft
1000 MHz	8.70 dB/100ft

## Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Impedence	Nom. Velocity
41.2 Ohm/1000ft	2.9 Ohm/1000ft	13.5 pF/ft	93 Ohm	84%

#### Voltage

Non-UL Voltage Rating 300 V

# **Mechanical Characteristics**

#### Temperature

Operating

-40°C to +75°C

#### Bend Radius

Installation Min. 2.4 in	
Bulk Cable Weight:	30 lbs/1000ft
Max. Pull Tension:	88 lbs

# **Standards and Compliance**

Environmental Suitability:	Outdoor - Aerial
Sustainability:	CA Prop 65
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
History	
Update and Revision:	Revision Number: 0.289 Revision Date: 10-16-2020

### Upd

© 2020 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.