

Product: [AV2183R](#) 

4K UHD Media Patch Cord CMR



Product Description

4K UHD Media Patch Cord, Shielded 4 Pair, 23 AWG Solid, CMR, T568A/B-T568A/B (cable 2183R)

Technical Specifications

Product Overview

Suitable Applications:	HDBaseT, Full 5-Play, 4K (UHD/DCI), POH, POE.
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4

Total Number of Pairs:	4
------------------------	---

Insulation

Material
PP - Polypropylene

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	26

Table Notes:	Drain wire applied helically for added flexibility
--------------	--

Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	.290 in.

Wiring Scheme:	T568A/B-T568A/B
----------------	-----------------

Packaging:	Individually packaged in a clear plastic bag.
------------	---

Connectors

Materials

Description	Material	Type
Plug	Polycarbonate	RJ45
Boot	Polycarbonate	
Front Connection	Phosphor Bronze with 50u inch Gold over Nickel Plating	Blades

Electrical Characteristics

Dielectric Strength:	1,000 V RMS @ 60 Hz for 1 minute
Current Rating:	1.500 A
Insulation Resistance:	500 M-Ohm Minimum
Max Contact Resistance:	20 mOhm

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)
-----------------	-----------------------------------

1 MHz	2.000 dB/100m
4 MHz	3.800 dB/100m
8 MHz	4.300 dB/100m
10 MHz	5.900 dB/100m
16 MHz	7.500 dB/100m
20 MHz	8.300 dB/100m
25 MHz	9.300 dB/100m
62.500 MHz	14.800 dB/100m
31.250 MHz	10.400 dB/100m
100 MHz	18.800 dB/100m
125 MHz	21.000 dB/100m
155 MHz	23.000 dB/100m
175 MHz	24.900 dB/100m
200 MHz	26.600 dB/100m
250 MHz	29.800 dB/100m
300 MHz	32.700 dB/100m
400 MHz	37.900 dB/100m
500 MHz	42.500 dB/100m

Temperature Range

Installation Temp Range:	-10°C To +60°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-10°C To +60°C

Mechanical Characteristics

Max. Pull Tension:	11.250 lbs
Min Bend Radius (Overall Cable):	2.200 in.
Plug /Jack Compatibility:	RJ45

Termination Interface

Termination	Connection	Durabilities
RJ45	Mated Connection	750 Cycles

Standards

NEC/(UL) Compliance:	CMR
CEC/C(UL) Compliance:	CMR
UL Rating:	Riser
Other Compliance:	FCC Part 68, Subpart F, IEC 60603-7, UL 1863 and CSA-22.2 No. 233

Applicable Environmental and Other Programs

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-01-01
MII Order #39 (China RoHS):	EUP 50

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Flammability, LSOH, Toxicity Testing

Safety Listing:	c(UL)us Listed
-----------------	----------------

Part Number

Variants

Item #	Color	Length
AV2183R100005	Black	5 ft
AV2183R100007	Black	7 ft
AV2183R100017	Black	17 ft
AV2183R100050	Black	50 ft
AV2183R106005	Blue, Light	5 ft
AV2183R106007	Blue, Light	7 ft
AV2183R106017	Blue, Light	17 ft

Product Notes

Labeling:	Belden Part Number, Performance Acronym, Wiring Scheme and Cord Length.
-----------	---

History

Update and Revision:	Revision Number: 0.58 Revision Date: 09-30-2020
----------------------	---

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.