



Product: <u>1048S</u> ☑

Inst, 2 Pr #18 Str BC, XLPE Ins E1, IS/OS, Blk LSZH Jkt, 600V TC 90C Dry/Wet

Product Description

UL Instrumentation, 2 Pair 18AWG (7x26) Bare Copper, XLPE Insulation E1 Color Code, Individual & Overall Beldfoil® Shield, Black LSZH Outer Jacket, 600V TC 90C Dry/Wet SUN RES

Technical Specifications

Physical Characteristics (Overall)

Condu	Conductor		
AWG	Stranding	Material	No. of Pairs
18	7x26	BC - Bare Copper	2
Condu	Conductor Count:		

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
XLP, XLPO, XLPE (Thermoset)	0.106 in	0.031 in

Color Chart

Number	Color	l
Pairs 1 & 2	ICEA S-73-732 Table E1: Black & White and Numbered	l

Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	20

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Таре	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	18

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
LSZH - Low Smoke Zero Halogen (Flame Retardant)	0.506 in	0.047 in

Electrical Characteristics

Conductor DCR

Individual Pair Nominal Shield DCR		Nominal Conductor DCR	Nominal Outer Shield DCR
	7.46 Ohm/1000ft	5.86 Ohm/1000ft	4.91 Ohm/1000ft

Current

Max. Recommended Current [A] 4.8 Amps per Conductor at 30°C

Voltage

UL Description	UL Voltage Rating	Voltage Rating [V]
TC	600 V RMS (Type TC)	600 V RMS (Type TC)

Temperature Range

Operating Temp Range:	-30°C To +90 °C Dry/Wet

Mechanical Characteristics

Bulk Cable Weight:	98 lbs/1000ft
Max. Pull Tension:	140 lbs
Min Bend Radius/Minor Axis:	5.1 in

Standards

NEC/(UL) Cor	mpliance:	TC, XHHW-2

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT4
IEEE Flammability:	1202
UL voltage rating:	600 V RMS (Type TC)

Product Notes

Notes:	Alternate color coding available upon request.

History

	Update and Revision:	Revision Number: 0.42 Revision Date: 09-30-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.