



**Product:** <u>6539Y8</u> ☑

**CCTV** Applications

# **Product Description**

Surveillance, CCTV & Card Reader Cable, RG62, Plenum-CMP, 22 AWG solid bare copper-covered steel, foamed polyolefin core, 95% bare copper braid, Flamarrest® jacket

# **Technical Specifications**

#### **Product Overview**

Suitable Applications:	Surveillance, CCTV Camera, Card Reader/Sensor

## **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding Material		Nominal Diameter	No. of Coax
22	Solid	BCCS - Bare Copper Covered Steel	0.025 in	1

#### Insulation

Material	Nominal Diameter
FEP - Fluorinated Ethylene Propylene (Foam)	0.146 in

## Outer Shield Material

Type Material		Coverage [%]
Braid	Bare Copper (BC)	95%

#### **Outer Jacket Material**

Material	Material Trade Name	Nominal Diameter
PVC - Polyvinyl Chloride	Flamarrest®	0.204 in

## **Electrical Characteristics**

### Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
41.2 Ohm/1000ft	41.2 Ohm/1000ft	3.4 Ohm/1000ft	3.4 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield 13.5 pF/ft

## Inductance

Nominal Inductance 0.107 µH/ft

## Impedance

Nominal Characteristic Impedance
93 Ohm

#### High Frequency (Nominal/Typical)

Frequency [MHz] Nom. Insertion Loss

1 MHz	0.3 dB/100ft
10 MHz	0.9 dB/100ft
50 MHz	1.9 dB/100ft
100 MHz	2.7 dB/100ft
200 MHz	3.8 dB/100ft
400 MHz	5.3 dB/100ft
700 MHz	7.3 dB/100ft
900 MHz	8.2 dB/100ft
1000 MHz	8.7 dB/100ft

## Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%	
1.21 ns/ft	84%	

## Voltage

UL Voltage Rating 300 V RMS

## **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

## **Mechanical Characteristics**

Bulk Cable Weight:	30 lbs/1000ft
Max. Pull Tension:	67 lbs
Min Bend Radius/Minor Axis:	2 in

## **Standards**

NEC/(UL) Compliance:	CMP
CEC/C(UL) Compliance:	CMP
RG Type:	62/U Type

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

# Suitability

Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes

# Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262
UL voltage rating:	300 V RMS

# Plenum/Non-Plenum

Plenu	um (Y/N):	Yes

## **Part Number**

## Variants

Item #	Color	Putup Type	Length	UPC
6539Y8 8771000	Natural	Reel	1,000 ft	612825178200

#### **Product Notes**

Notes:	Print legend includes sequential footage marks.

#### **History**

Update and Revision:	Revision Number: 0.230 Revision Date: 09-30-2020

#### © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.