

Product: 8428 ☑

Microphone Cable, 2 Conductor 18 AWG, TC



Product Description

18 AWG stranded (41x34) High-conductivity TC conductors, EPDM rubber insulation, rayon braid, TC braid shield (85% coverage), cotton wrap, CPE jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor					
AWG	Stranding	Material		Nominal Diameter	No. of Conductors
18	41x34	TC - Tinned Copper (High Conductivity)		0.047 in	2
Conductor Count:		2			

Insulation

	Material	Nominal Diameter	Nominal Wall Thickness
E	EPDM - Ethylene Propylene Diene Monomer	0.1 in	0.0235 in

Color Chart

Number	Color
1	White
2	Black

Outer Shield Material

Type	Material	Coverage [%]
Braid	Rayon®	85%
Braid	Tinned Copper (TC)	85%

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Separator Material
CPE - Chlorinated Polyethylene	0.29 in	0.030 in	Cotton Serve

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR
6.8 Ohm/1000ft	6.8 Ohm/1000ft	2.7 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
35 pF/ft	60 pF/ft

Inductance



Impedance

Nominal Characteristic Impedance

Current

Max. Recommended Current [A]

5.2 Amps per Conductor at 25°C

Voltage

Non-UL Voltage Rating

600 V RMS

Temperature Range

Non-UL Temp Rating:	60°C
Operating Temp Range:	-30°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	54 lbs/1000ft
Max. Pull Tension:	138 lbs
Min Bend Radius/Minor Axis:	3 in

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
1 10114111 (1711).	

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
8428 010100	Black	Reel	100 ft	612825206880
8428 010500	Black	Reel	500 ft	612825206866
8428 010U50	0 Black	UnReel	500 ft	612825206989
8428 010100	0 Black	Reel	1,000 ft	612825206897

Footnote:

Update and Revision:	Revision Number: 0.310 Revision Date: 09-30-2020

C - CRATE REEL PUT-UP.

© 2020 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.