


Product: [MRG5800](#) 



COAX RF RG58 PVC

 [Request Sample](#)

## Product Description

COAX RF [0.9/2.95] RG58 STRANDED PVC

## Technical Specifications

### Product Overview

Suitable Applications:	Coaxial communication cable based on MIL-C-17
------------------------	---

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Construction n x D	Diameter +/- Tolerance	No. of Coax
21	Stranded	TC - Tinned Copper	19x0.18 mm	0.02 mm	1

Conductor Count:	1
------------------	---

#### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene	2.95 mm	0.15 mm

#### Outer Shield Material

Type	Material	Coverage [%]	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Braid	Tinned Copper (TC)	93%	3.5 mm	0.2 mm	4%

#### Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	4.95 mm	0.2 mm

Table Notes:	According to EN 50290-2-20
--------------	----------------------------

### Construction and Dimensions

Min Elongation at Breakof Jacket:	150 %
Min Tensile Strength of Jacket:	12.5 MPa

### Electrical Characteristics

#### Conductor DCR

Max. Conductor DCR
40.6 Ohm/km

#### Capacitance

Nom. Capacitance	Capacitance Tolerance
100 pF/m	2 pF/m

#### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
50 Ohm	2 Ohm	Min. 40 dB

### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
10 MHz	4.7 dB/100m
200 MHz	23 dB/100m
400 MHz	34 dB/100m
1000 MHz	60 dB/100m

Table Notes: Max. attenuation 10% higher

### Delay

Nominal Velocity of Propagation (VP) [%]
66%

### High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 30 MHz	20 dB
30 - 470 MHz	20 dB
470 - 1000 MHz	18 dB

Table Notes: In each frequency band, 3 peak values up to 4 dB lower are allowed

### Voltage

Voltage Rating [V]
4000 DC / 2000 V RMS

### Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

### Mechanical Characteristics

Min Bend Radius (W/o Pulling Strength):	25 mm
Crush Resistance:	Max. 1% (load of 700N) N

### Standards

CPR Euroclass:	Eca
CENELEC Compliance:	EN 50290-2-20 and EN 50289
RG Type:	58/U Type
Military Compliance:	MIL-C-17

### Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Eca
EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01

### Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
-------------------	---------------

### Part Number

#### Variants

Item #	Color	Putup Type	Length	EAN
MRG5800.10100	Black	Reel	100 m	8719605103239
MRG5800.00B200	Black	Flat Box	200 m	8719605103208
MRG5800.00500	Black	Reel	500 m	8719605103192
MRG5800.01500	Black	Reel	500 m	8719605103215
MRG5800.12100	White	Reel	100 m	8719605103246
MRG5800.02500	White	Reel	500 m	8719605103222

### History

Update and Revision:	Revision Number: 0.162 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.