



Product: <u>5200FL</u> ☑

Fire Alarm, #16-2c BC, Shielded, FPLR

# **Product Description**

Fire Alarm Cable, Riser-FPLR, 2-16 AWG stranded bare copper conductors with polyolefin insulation, overall Beldfoil® shield, PVC jacket with ripcord

## **Technical Specifications**

## **Product Overview**

Suitable Applications:	Fire Alarm, Monitor/Detection, Circuits: Audio, Control, Initiating, Notification, Noisy Environment
BI : 101	n.

## **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	No. of Conductors
16	19x29	BC - Bare Copper	2
Condu	uctor Count:		2

### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.008 in

### **Color Chart**

Number	Color
1	Black
2	Red

### Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	24	Solid

### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.184 in	0.017 in	Yes

## **Construction and Dimensions**

### Cabling



## **Electrical Characteristics**

### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
4.2 Ohm/1000ft	16 Ohm/1000ft

## Capacitance

Nom. Capacitance Conductor to Conductor Nom. Capacitance Conductor to Other Conductor to Shield

#### Current

Max. Recommended Current [A]
11 Amps per Conductor at 25°C

### Voltage

UL Voltage Rating 300 V RMS

### **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

### **Mechanical Characteristics**

Bulk Cable Weight:	24 lbs/1000ft
Max. Pull Tension:	61 lbs
Min Bend Radius/Minor Axis:	1.875 in

#### **Standards**

NEC Articles:	Article 760
NEC/(UL) Compliance:	FPLR

### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2009-10-01
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1666 Riser
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6200FL

### **Part Number**

### Variants

Item #	Color	UPC
5200FL 0021000	Red	612825157373
5200FL 002U1000	Red	612825157366

Footnote: C - CRATE REEL PUT-UP.

## **History**

Update and Revision:	Revision Number: 0.237 Revision Date: 09-30-2020

## © 2020 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief

at the date of its publication. This information is d Disclosure is not to be considered a warranty or or regulations based on their individual usage of the	esigned only as a general guide for the sat yuality specification. Regulatory information product.	fe handling, storage, and any othen n is for guidance purposes only. Pr	r operation of the product itself or tr oduct users are responsible for det	ne one that it becomes a part of. T ermining the applicability of legisla	ne Product ition and