



# Product: <u>5122FN</u> 2

Fire Alarm, #14-4c BC, Shielded, NPLF

## **Product Description**

Fire Alarm Cable, Rated-NPLF, 4-14 AWG solid bare copper conductors with PVC/nylon insulation, overall Beldfoil® shield, PVC jacket with ripcord

#### **Technical Specifications**

#### **Product Overview**

Suitable Applications: Fire Alarm, Non-Power					wer Limited,	Circuits: Auc	lio, Control, Init	iating, Notifica	ation, Noisy Env
ys	ical Char	acteristics (Ov	/era	il)					
ondu	ctor								
AWG	Stranding	Material	No.	of Conductors					
14	Solid	BC - Bare Copper	4						
Condu	ctor Count:			4					
nsulat	ion								
	Ma	terial	No	minal Wall Thickne	ss				
PVC/Nylon - Polyvinyl Chloride + Nylon 0.0		21 in							

Number	COIOI
1	Black
2	Red
3	Brown
4	Blue

#### **Outer Shield Material**

Туре	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Таре	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	20	Solid

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.348 in	0.042 in	Yes

## **Construction and Dimensions**

## Cabling

Twists

3 twist/ft

#### **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
2.46 Ohm/1000ft	6.9 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
37.7 pF/ft	67.9 pF/ft

#### Current

Max. Recommended Current [A]
6.4 Amps per Conductor at 25°C

#### Voltage

UL Voltage Rating 150 V RMS

#### **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	93.9 lbs/1000ft
Max. Pull Tension:	212.8 lbs
Min Bend Radius/Minor Axis:	3.5 in

#### **Standards**

NEC Articles:	Article 760
NEC/(UL) Compliance:	NPLF

#### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-07-01
MII Order #39 (China RoHS):	Yes

#### Suitability

Suitability - Indoor:	Yes	

#### Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
UL voltage rating:	150 V RMS
Plenum/Non-Plenum	

Plenum (Y/N):	No

## Part Number

#### Variants

Item #	Color	UPC
5122FN 0021000	Red	612825157052
5122FN 002500	Red	612825157069

#### **History**

Update and Revision:

Revision Number: 0.233 Revision Date: 09-30-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.