



Product: <u>1311A</u> ☑

Speaker Cable, 2 C #12 Str BC-OFHC, PVC Jkt, CM, DIR BUR, Flexible

Product Description

Speaker Cable, 2 Conductor 12 AWG (168 x 34) Oxygen-Free Bare Copper (High Conductivity), PE Insulation, PVC Jacket, CM, Direct Burial, Flexible

Technical Specifications

Product Overview

Suitable Applications:		:	Speaker Cable; Direct Burial; Indoor/Outdoor Home Theater; In-Wall Speaker; Outdoor Speaker					
Constructi	on Deta	ils						
Conductor								
Element	Number o	f Elemen	t AWG	Stranding	Material			
Conductor(s)	2		12	168x34	BC - Bare Copper (High Conductivity)		tivity)	
nsulation Element	Mater	ial	Thicknes	s Nom In	sulation Diameter	Color Code	I	
Conductor(s)	PE - Polye		0.018 in	0.14		Black, Red		
Duter Jacket N	A aterial							
Material Thickn		Thickne	ess Nom. Diameter					
PVC - Polyvinyl Chloride 0.036 in		0.036 in	n 0.352 in					
Cable Diameter (Nominal): 0.352			0.352 in					

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Velocity of Prop.	Max. Current
Conductor(s)	1.6 Ohm/1000ft	22.3 pF/ft	66%	17 Amps per conductor @ 25°C

Voltage

UL Voltage Rating 300 V (CM, CL3)

Mechanical Characteristics

UL Rating 75°C	Operating -20°C To +75°C	
Bend Radiu	-	
3.5 in	Min. Installation M 3.5 in	
Max. Pull Te	ension:	152 lbs
Bulk Cable Weight:		67 lbs/1000ft

JL1666 Riser, IEC 60332-1-2
Article 725, Article 800, CL3, CM
CM
ca
U Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
China RoHS II (GB/T 26572-2011)
000UE

Product Notes

Notes:	Jacket has ROOM 1 2 3 4 5 6 7 8 9 0 ZONE A B C D printed on it.

History

Update and Revision:

Revision Number: 0.317 Revision Date: 09-30-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.