

# Product: <u>70072CH</u> ☑



# 12 PAIR AES/EBU, 22AWG, ISTP, LSZH-C

# **Product Description**

DIGITAL AUDIO 12 PAIR AES/EBU, 22AWG/0.34mm², ISTP, LSZH-C

### **Technical Specifications**

#### **Product Overview**

Suitable Applications:	Digital multi-modulation cable used in professional studios for the transmission of analogue and digital audio signals.; Designed to meet the requirements of the AES/EBU specification				
Physical Characteristics (Overall)					

#### Conductor

AWG	Stranding	Material		No. of Pairs
22	7x30 BC-OFHC - Oxygen-Free Bare Copper (High Conductivity)		12	
Conductor Count:			24	
Total Number of Pairs:		airs:	12	

#### Insulation

Material	Nominal Diameter	Diameter +/- Tolerance	
PE - Polyethylene (Foam)	2.1 mm	0.05 mm	

#### Color Chart

 Number
 Color

 Pair 1 t/m 12
 Red & Black

#### Inner Shield Material

Туре	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Position
Таре	Bi-Laminate (Alum+Poly)	100%	Stranded tinned copper	22	Under shielding foil

#### Inner Jacket Material

	Material		Nominal Diameter	Diameter +/- Tolerance
LSZH - Low Smoke Zo	ero Halogen (Flame	e Retardant)	5.3 mm	0.1 mm
Table Notes:		Elements	are numbered for ide	entification

#### **Outer Shield Material**

Material

Bi-Laminate (Alum+Poly)

#### Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
LSZH - Low Smoke Zero Halogen (Flame Retardant)	24.6 mm	0.1 mm

## **Construction and Dimensions**

Cabling

Description

1 center filler + 12 pairs + stranded tinnend copper drainwire (22AWG)(7x0.25) covered with a non-woven foil

#### **Electrical Characteristics**

# Conductor DCR Nominal Conductor DCR 86 Ohm/km Capacitance Nom. Capacitance Conductor to Conductor 40 pF/m Impedance Nominal Characteristic Impedance Nominal Characteristic Tolerance 110 Ohm 15 Ohm **Temperature Range** Other Temp Range: -30-+70 °C **Mechanical Characteristics** Min Setting Radius: 123 mm **Standards** CPR Euroclass: Eca **Applicable Environmental and Other Programs** Environmental Space: Indoor - Euroclass Eca EU RoHS Compliance Date 2014-12-02 (yyyy-mm-dd):

#### Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2 and IEC 60332-3-24
IEC 60754-1 (EN50267-1)- Halogen Amount:	Zero

#### Part Number

#### Variants

Item #	Color	Putup Type	Length	EAN
70072CH.00500	Gray	Reel	500 m	8719605124067

#### History

Update and Revision:

Revision Number: 0.111 Revision Date: 08-25-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.