



Product: [1805F](#)

Audio Snake Cable, #24-8pr, TC, Individ. Shielded, CMG

Product Description

Digital Audio Snake Cable, CMG-Rated, 8-24 AWG tinned copper pairs, Datalene® insulation, individually shielded with Beldfoil, numbered/color-coded PVC jackets, flexible PVC jacket

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
24	7x32	TC - Tinned Copper	0.024 in	8

Conductor Count:	16
Total Number of Pairs:	8

Insulation

Material	Material Trade Name	Nominal Diameter
PE - Polyethylene (Foam)	Datalene®	0.068 in

Color Chart

Number	Color
1	Red & Black
2	Red & Black
3	Red & Black
4	Red & Black
5	Red & Black
6	Red & Black
7	Red & Black
8	Red & Black

Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire AWG	Drainwire Construction n x D
Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	24	Stranded

Table Notes:	Indiv. Foil tapes bonded to inner jacket
--------------	--

Inner Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.167 in

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	16	Stranded

Outer Jacket Material

Material	Nominal Diameter	Ripcord
PVC - Polyvinyl Chloride	0.661 in	Yes

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR

23.7 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
12 pF/ft	26 pF/ft

Inductance

Nominal Inductance

0.18 μ H/ft

Impedance

Nominal Characteristic Impedance

110 Ohm

High Frequency (Nominal/Typical)

Nom. Insertion Loss

0.46 dB/100ft

0.67 dB/100ft

0.7 dB/100ft

0.84 dB/100ft

1.03 dB/100ft

1.09 dB/100ft

1.3 dB/100ft

1.66 dB/100ft

1.76 dB/100ft

2.23 dB/100ft

2.9 dB/100ft

3.07 dB/100ft

3.71 dB/100ft

4.53 dB/100ft

4.78 dB/100ft

7.11 dB/100ft

High Freq

Frequency [MHz]

0.384 MHz

0.7056 MHz

0.768 MHz

1.024 MHz

1.4112 MHz

1.536 MHz

2.048 MHz

2.8224 MHz

3.072 MHz

4.096 MHz

5.6448 MHz

6.144 MHz

8.192 MHz

11.2896 MHz

12.288 MHz

24.576 MHz

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

UL Temp Rating: 60°C

Operating Temp Range:	-30°C To +60°C
-----------------------	----------------

Mechanical Characteristics

UV Resistance:	No
Bulk Cable Weight:	195 lbs/1000ft
Max. Pull Tension:	137 lbs
Min Bend Radius/Minor Axis:	6.75 in

Standards

NEC/(UL) Compliance:	CMG
CEC/C(UL) Compliance:	CMG
CPR Euroclass:	Eca
Other Compliance:	AES/EBU

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
1805F Z4B3000	Violet	Reel	3,000 ft	612825438205
1805F Z4B500	Violet Z4B	Reel	500 ft	612825123187
1805F Z4B1000	Violet Z4B	Reel	1,000 ft	612825123170

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

Product Notes

Notes:	Pair jackets and shields are bonded so both strip simultaneously with automatic stripping equipment. Datalene« insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.
--------	---

History

Update and Revision:	Revision Number: 0.298 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.