



Product: <u>8404</u> ☑

Microphone Cable, Star Quad, 4 C #20 Str TC, Rayon & 85% TC Braid, PVC

Product Description

Microphone Cable, Star Quad, 4 Conductor 20 AWG (19 x 32) Tinned Copper (High conductivity), PE Insulation, Rayon® Braid, 85% Tinned Copper Braid Shield, PVC jacket

Technical Specifications

Product Overview

Suitable Applications: Low frequency microphone or musical instruments; Balanced analog audio; Low Noise for high-EMI environments

Construction Details

Conductor

Element	Number of Element	AWG	Stranding	Material
Conductor(s)	4	20	19x32	TC - Tinned Copper (High Conductivity)

Insulation

Element	Material	Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	PE - Polyethylene	0.016 in	0.069	Clear, Black, Red, Green

Outer Shield Material

Shield Type	Material	Coverage
Braid + Braid	Rayon® + Tinned Copper (TC)	85% + 85%

Outer Jacket Material

Material	Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.032 in	0.252 in
Cable Diameter (Nominal):	0.252 in	

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Characteristic Impedence	Nom. Velocity of Prop.	Max. Current	
Conductor(s)	10.2 Ohm/1000ft	23 pF/ft	45 Ohm	66%	3.1 Amps per conductor @ 25°C	
Nom Outer Sh	Nom Outer Shield DCR: 3.23 Ohm/1000ft					

Voltage

UL Voltage Rating 300 V (UL AWM 2094)

Mechanical Characteristics

Temperature

UL Rating	Operating
60°C (UL AWM 2094)	-20°C to +60°C

Bend Radius

2 F im 2 im	Stationary Min.	Installation Min.
2.5 111 3 111	2.5 in	3 in

Max. Pull Tension:	100 lbs
Bulk Cable Weight:	46 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Flammability / Fire Resistance:	VW-1
AWM Compliance:	2094
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	Overall cabling separator material: Rayon braid. Quad connection scheme: The two blue wires (or wires directly opposite one another) are connected together to form one conductor, and similarly the two white wires (or remaining wires) are connected together to form the second conductor.

History

Update and Revision:	Revision Number: 0.335 Revision Date: 09-30-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.