



Product: [7960A](#)

DataTuff® Cat 5e, Quad (2 Pr) #22 Sol BC, PO Ins, OS+TC Brd, PVC Jkt, CMG CMX-Outdoor

[Request Sample](#)

Product Description

Industrial Ethernet Cat 5e, Quad (2 Pair) 22AWG (Solid) Bare Copper, PO Insulation, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, PVC Outer Jacket, CMG CMX-Outdoor

Technical Specifications

Product Overview

Suitable Applications:	PROFINET, outdoor, harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc.
------------------------	---

Construction Details

Conductor

AWG	Stranding	Material	Number of Conductors
22	Solid	BC - Bare Copper	4

Insulation

Material	Color Code
PO - Polyolefin	White, Blue, Yellow, Orange

Bonded-Pair:	No
--------------	----

Inner Jacket Material

Material	Nom. Diameter
PE - Polyethylene	0.164 in

Outer Shield Material

Type	Material	Coverage
Tape	Bi-Laminate (Alum+Poly)	100%
Braid	Tinned Copper (TC)	85%

Outer Jacket Material

Material	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.265 in	No

Electrical Characteristics

Electricals

Max. Conductor DCR	Max. DCR Unbalance	Max. Capacitance Unbalance	Nom. Mutual Capacitance
5.7 Ohm/1000ft	3%	150 pF/ft	15 pF/ft

Delay

Max. Delay	Nom. Velocity of Propagation (VP) [%]
552 ns/100m	70%

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance
1 MHz	2.1 dB/100m	65.3 dB	62.3 dB	63.2 dB	63.8 dB	60.8 dB	23 dB	100 ± 20.2 Ohm	105 ± 10 Ohm

4 MHz	4.0 dB/100m	56.3 dB	53.3 dB	56.3 dB	51.7 dB	48.7 dB	23 dB	100 ± 14.2 Ohm	100 ±10 Ohm
8 MHz	5.6 dB/100m	51.8 dB	48.8 dB	46.2 dB	45.7 dB	42.7 dB	23 dB	100 ± 11.3 Ohm	100 ±10 Ohm
10 MHz	6.3 dB/100m	50.3 dB	47.3 dB	43.9 dB	43.8 dB	40.8 dB	25 dB	100 ± 11.3 Ohm	100 ±10 Ohm
16 MHz	8.0 dB/100m	47.3 dB	44.3 dB	35.2 dB	39.7 dB	36.7 dB	25 dB	100 ± 11.3 Ohm	100 ±10 Ohm
20 MHz	9.0 dB/100m	45.8 dB	42.8 dB	36.5 dB	37.7 dB	34.7 dB	25 dB	100 ± 11.3 Ohm	100 ±10 Ohm
25 MHz	10.1 dB/100m	44.3 dB	41.3 dB	34.2 dB	35.8 dB	32.8 dB	25.5 dB	100 ± 11.3 Ohm	100 ±10 Ohm
31.25 MHz	11.4 dB/100m	42.9 dB	39.9 dB	31.3 dB	33.9 dB	30.9 dB	23.6 dB	100 ± 13.2 Ohm	100 ±10 Ohm
62.5 MHz	16.5 dB/100m	38.4 dB	35.4 dB	21.6 dB	27.8 dB	24.8 dB	21.5 dB	100 ± 16.9 Ohm	100 ±10 Ohm
100 MHz	21.3 dB/100m	35.3 dB	32.3 dB	17.1 dB	23.8 dB	20.8 dB	20.1 dB	100 ± 20.0 Ohm	100 ±10 Ohm

Voltage

UL Voltage Rating
300 V (CMG, CMX-Outdoor), 600 V (AWM 21047)

Mechanical Characteristics

Temperature

UL Rating	Operating	Installation	Storage
60°C	-40°C To +80°C	-25°C To +60°C	-40°C To +80°C

Bend Radius

Stationary Min.
2.560 in

Max. Pull Tension:	55 lbs
Bulk Cable Weight:	40.7 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Oil Resistance
Flammability / Fire Resistance:	UL 1685 (UL Loading), FT4, FT4, 1202 Vertical Tray, IEC 60332-1-2
NEC / UL Compliance:	800, CMG;CMX-Outdoor;ITC;PLTC
AWM Compliance:	21047
CEC / C(UL) Compliance:	CMX-Outdoor;CMG
NEMA Compliance:	NEMA WC-63.1
Data Category:	Category 5e
TIA/EIA Compliance:	ANSI/TIA-568.2-D Category 5e
CPR Euroclass:	Eca
European Directive Compliance:	EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Part Number

Variants

Item #	Color	Putup Type	Length	UPC/EAN
7960A.00305	Green	Reel	305 m	8719605016775
7960A.00610	Green	Reel	610 m	8719605016782
7960A 1SW1000	Green, RAL 6018			612825367291
7960A 1SW2000	Green, RAL 6018			612825367307

Product Notes

Notes:	Operating Temperature subject to length de-rating. Cable passes -40C Cold Bend per UL 1581. Limits below 4 MHz are for information only.
--------	--

History

Update and Revision:	Revision Number: 0.253 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and

regulations based on their individual usage of the product.