



Product: 82760 ☑

Electronic, 2 C #18 Str TC, FEP Ins, OS, PVC Jkt, CMP

Product Description

Electronic Cable, 2 Conductor 18AWG (19x30) Tinned Copper, FEP Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CMP

Technical Specifications

Product Overview

Suitable Applications: indoor plenum applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; voice communications; panel wiring

Construction Details

Conductor

Element	Number of Element	AWG	Stranding	Material
Pair(s)	1	18	19x30	TC - Tinned Copper

Insulation

Element	Material	Thickness	Color Code
Pair(s)	FEP - Fluorinated Ethylene Propylene	0.007 in	Black, Red

Outer Shield Material

Shield Type	Material	Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	20 AWG (7x28) TC

Outer Jacket Material

Material	Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.014 in	0.146 in
Cable Diameter (Nominal	I): 0	.146 in

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Characteristic Impedence	Nom. Velocity of Prop.	Max. Current
Pair(s)	5.5 Ohm/1000ft	51 pF/ft	97 pF/ft	35 Ohm	69%	5.4 Amps per Conductor at 25°C
Nom Out	ter Shield DCR:	7.3 Ohm/1000ft				

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature



Bend Radius

Stationary Min. Installation Min.

1.5 in	1.5 in	
Max. Pull Ten	sion:	62 lbs
Bulk Cable W	eight:	20 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor	
Flammability / Fire Resistance:	NFPA 262 Plenum Flame Test (UL910), FT6, IEC 60332-1-2	
NEC / UL Compliance:	Article 800, CMP	
CEC / C(UL) Compliance:	CMP	
CPR Euroclass:	Eca	
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	
Non-Plenum Number:	8760	

History

Update and Revision:	Revision Number: 0.376 Revision Date: 09-30-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.