

Product: <u>6341PT</u> ⊠ Thermostat & Control, #18-2pr, TC, Indiv. Foil, CMP

Product Description

Thermostat & Control Cable, Plenum-CMP, 2-18 AWG stranded tinned copper pairs with foam FEP insulation, Individually Beldfoil® shielded and Flamarrest® jacket

Technical Specifications

Product Overview

Suitab								
	le Applicatio	ns:				Thermostat, Control, Nois	y Environment	
Phys	ical Char	acteristic	s (Ovei	rall)				
Condu	ctor							
AWG	Stranding	Materi	ial	No. of Pair	s			
18	7x26	TC - Tinned	Copper	2				
Condu	uctor Count:					4		
nsulat	ion							
		Material						
FEP -		Ethylene Prop	vlene (Eo	am)				
	T luointatou l	Latytone i rop	sylonic (i c	anny				
Color C	Chart							
Numb	er Colo	or						
Numb	Black &							
		White						
1 2	Black & Green &	White Red						
1 2 Outer S	Black & Green & Shield Mater	White Red ial						
1 2	Black & Green & Shield Mater Mat	White Red ial terial	Materia	l Trade Nar	me Coverag	e [%] Drainwire Materia	I Drainwire AWG	Drainwire Construction n x
1 2 Outer S	Black & Green & Shield Mater	White Red rial cerial	Materia Beldfoil		me Coverag	e [%] Drainwire Materia TC - Tinned Copp		Drainwire Construction n x 7x26
1 2 Duter S Type Tape	Black & Green & Shield Mater Mat	White Red rial	_					
1 2 Duter S Type Tape	Black & Green & Shield Mater Mat Bi-Laminate (Alum+Poly	White Red ial erial	_	Ð		TC - Tinned Copp		

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR

6.6 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor 13.7 pF/ft

Inductance

Nominal Inductance

Delay

Max. Delay Skew

78 ns/100m

High Freq

Max./Min. Input Impedance (unFitted) 100 ± 10 Ohm

Current

Max. Recommended Current [A] 8.1 Amps per Conductor at 25°C

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	56 lbs/1000ft
Max. Pull Tension:	134 lbs
Min Bend Radius/Minor Axis:	2.8 in

Standards

NEC/(UL) Compliance:	СМР
CEC/C(UL) Compliance:	СМР

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-02-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262 Plenum Flame Test (UL910)
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	Yes

Part Number

Variants		
Item #	Color	UPC
6341PT 0011000	Brown	612825176299
Footnote:		
istory		
Update and Revi	sion:	

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.