



Product: <u>8407</u> ☑

Microphone Cable, Star Quad, 4 C #16 Str TC, Rayon & 85% TC Braid, Cotton Serve, CPE Jkt

Product Description

Microphone Cable, Star Quad, 4 Conductor 16 AWG (65 x 34) Tinned Copper (High conductivity), EPDM Insulation, Rayon® Braid, 85% Tinned Copper Braid Shield, Cotton Serve, CPE Jacket

Technical Specifications

Product Overview					
Suitable Applications:	Low frequency mic	o; Low Noise for high-EMI er			
Construction Deta	ills				
Conductor					
Element Number Conductor(s) 4	of Element AWG St 16 65			laterial per (High Conductivity)	
Insulation					
Element Conductor(s) EPDM - E	Material Ethylene Propylene Die	ne Monomer		Nom. Insulation Diameter 0.12	Color Code Black, White, Red, Green
Outer Shield Material					
Shield TypeBraid + BraidRayon® -	Material + Tinned Copper (TC)	Coverage 85% + 85%			
Outer Jacket Material					
Separator Cotton Serve CPE - Ch	Material lorinated Polyethylene		Nom. Diame	ter	
Cable Diameter (Nomina					
Electrical Charact					

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Characteristic Impedence	Nom. Velocity of Prop.	Max. Current
Conductor(s)	4 Ohm/1000ft	30 pF/ft	44 Ohm	52%	5.6 Amps per conductor at 25°C
Nom Outer Shield DCR: 2.63 Ohm/1000ft					

Voltage

Non-UL Voltage Rating 600 V

Mechanical Characteristics

Temperature

Operating -30°C to +60°C

Bend Radius

Stationary Min. Installation Min.

4.25 in	5 in	
Max. Pull Tensior	า:	162 lbs
Bulk Cable Weigh	nt:	111 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Flammability / Fire Resistance:	VW-1
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	Quad connection scheme: The black and red wires (or wires directly opposite one another) are connected together to form one conductor, and similarly the white and green wires (or remaining wires) are connected together to form the second conductor.				
History					
Update and Revision:	Revision Number: 0.344 Revision Date: 09-30-2020				

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.