



Product: [153076F](#)

Fieldbus, 1 Pr #18 Str TC, PP ins, OS, PVC Jkt, CST Armor, PVC Jkt, PLTC
ISA/SP-50 Type A, PLTC

Product Description

Fieldbus, 1 Pair 18AWG (7x26) Tinned Copper, PP insulation, Overall Beldfoil® Shield, PVC Inner Jacket, Steel Corrugated Tape Armor, PVC Outer Jacket, PLTC ISA/SP-50 Type A, PLTC

Technical Specifications

Suitable Applications: harsh environment digital and serial two-way communication, oil and gas extraction and refining sites, petrochemical, Profibus process automation or Foundation FieldBus process automation, extreme temperature environments, exposure to humidity/moisture, dust, and oil, remote locations long distance applications, etc.

Conductor

Element	Number of Element	AWG	Stranding	Material
Pair(s)	1	18	7x26	TC - Tinned Copper

Insulation

Element	Material	Thickness	Color Code
Pair(s)	PP - Polypropylene	0.022 in	Blue & Orange

Outer Shield Material

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	20 AWG (7x28) TC

Inner Jacket Material

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.280 in

Armor

Armor Type & Material
CST - Corrugated Steel Tape

Outer Jacket Material

Material	Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.050 in	0.430 in

Cable Diameter (Nominal): 0.430 in

Electricals

Element	Characteristic Impedance	Nom. Velocity of Prop.
Pair(s)	100 Ohm	66%

High Frequency (Nominal/Typical)

Element
Pair(s)

Voltage

UL Voltage Rating
300 V (PLTC)

Temperature

UL Rating

105°C

NEC / UL Compliance:	Article 725, PLTC
Other Standard Compliance(s):	ISA/SP-50 Type A
Update and Revision:	Revision Number: 0.36 Revision Date: 09-30-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.