



REPRESENTATIVE IMAGE

Product: [2183P](#)

4K UHD Media Cable, 4 Pr #23, F/UTP Flamarrest® Jacket, CMP

Product Description

4 Pair 23 AWG Solid Bare Copper Conductors, FEP Insulation, F/UTP, Helical TC Drain, Ripcord, Flamarrest® Jacket, Plenum CMP-LP (0.6A)

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | HDBaseT, Full 5-Play, 4K (UHD/DCI), POH, POE |
|------------------------|--|

Physical Characteristics (Overall)

Conductor

| Element | AWG | Stranding | Material | No. of Pairs |
|---------|-----|-----------|------------------|--------------|
| Pair(s) | 23 | Solid | BC - Bare Copper | 4 |

| | |
|------------------------|---|
| Conductor Count: | 8 |
| Total Number of Pairs: | 4 |

Insulation

| Element | Material | Nominal Wall Thickness |
|---------|--------------------------------------|------------------------|
| Pair(s) | FEP - Fluorinated Ethylene Propylene | 0.010 in |

| | |
|--------------|-----|
| Bonded-Pair: | Yes |
|--------------|-----|

Color Chart

| Number | Color |
|--------|------------------------------|
| 1 | White/Blue Stripe & Blue |
| 2 | White/Orange Stripe & Orange |
| 3 | White/Green Stripe & Green |
| 4 | White/Brown Stripe & Brown |

Outer Shield Material

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG |
|------|-------------------------|---------------------|--------------|--------------------|---------------|
| Tape | Bi-Laminate (Alum+Poly) | Beldfoil® | 100% | TC - Tinned Copper | 26 |

Outer Jacket Material

| Material | Material Trade Name | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|--------------------------|---------------------|------------------|------------------------|---------|
| PVC - Polyvinyl Chloride | Flamarrest® | 0.270 in | 0.018 in | Yes |

Electrical Characteristics

Conductor DCR

| Max. Conductor DCR | Max. DCR Unbalance |
|--------------------|--------------------|
| 93.8 Ohm/km | 5 % |

Capacitance

| Max. Capacitance Unbalance | Nom. Mutual Capacitance |
|----------------------------|-------------------------|
| 330 pF/100m | 15 pF/ft |

High Frequency (Nominal/Typical)

| Frequency [MHz] | Nom. Insertion Loss |
|-----------------|---------------------|
| 1 MHz | 2 dB/100m |
| 4 MHz | 3.8 dB/100m |
| 8 MHz | 4.3 dB/100m |
| 10 MHz | 5.9 dB/100m |
| 16 MHz | 7.5 dB/100m |
| 20 MHz | 8.3 dB/100m |
| 25 MHz | 9.3 dB/100m |
| 31.2 MHz | 10.4 dB/100m |
| 62.5 MHz | 14.8 dB/100m |
| 100 MHz | 18.8 dB/100m |
| 125 MHz | 21 dB/100m |
| 155 MHz | 23 dB/100m |
| 175 MHz | 24.9 dB/100m |

Delay

| Frequency [MHz] | Max. Delay | Max. Delay Skew |
|-----------------|---------------|-----------------|
| 100 MHz | 537.6 ns/100m | 45 ns/100m |

High Freq

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. NEXT [dB] | Min. PSNEXT [dB] | Min. ACR [dB] | Min. PSACR [dB] | Min. ACRF (ELFEXT) [dB] | Min. PSACRF (PSELFEXT) [dB] | Min. RL (Return Loss) [dB] | Max./Min. Input Impedance (unFitted) |
|-----------------|-----------------------------------|----------------|------------------|---------------|-----------------|-------------------------|-----------------------------|----------------------------|--------------------------------------|
| 1 MHz | 2.0 dB/100m | 65.3 dB | 62.3 dB | 63.3 dB | 60.3 dB | 63.8 dB | 60.8 dB | 20.0 dB | 100 +/- 15 |
| 4 MHz | 3.8 dB/100m | 56.3 dB | 53.3 dB | 52.5 dB | 49.5 dB | 51.8 dB | 48.8 dB | 23.0 dB | 100 +/- 15 |
| 8 MHz | 5.3 dB/100m | 51.8 dB | 48.8 dB | 46.5 dB | 43.5 dB | 45.7 dB | 42.7 dB | 24.5 dB | 100 +/- 15 |
| 10 MHz | 5.9 dB/100m | 50.3 dB | 47.3 dB | 44.4 dB | 41.4 dB | 43.8 dB | 40.8 dB | 25.0 dB | 100 +/- 15 |
| 16 MHz | 7.5 dB/100m | 47.2 dB | 44.2 dB | 39.8 dB | 36.8 dB | 39.7 dB | 36.7 dB | 25.0 dB | 100 +/- 15 |
| 20 MHz | 8.4 dB/100m | 45.8 dB | 42.8 dB | 37.4 dB | 34.4 dB | 37.8 dB | 34.8 dB | 25.0 dB | 100 +/- 15 |
| 25 MHz | 9.3 dB/100m | 44.3 dB | 41.3 dB | 35.0 dB | 32.0 dB | 35.8 dB | 32.8 dB | 24.3 dB | 100 +/- 15 |
| 31.25 MHz | 10.5 dB/100m | 42.9 dB | 39.9 dB | 32.4 dB | 29.4 dB | 33.9 dB | 30.9 dB | 23.6 dB | 100 +/- 15 |
| 62.5 MHz | 14.8 dB/100m | 38.4 dB | 35.4 dB | 23.6 dB | 20.6 dB | 27.9 dB | 24.9 dB | 21.5 dB | 100 +/- 15 |
| 100 MHz | 18.8 dB/100m | 35.3 dB | 32.3 dB | 16.5 dB | 13.5 dB | 23.8 dB | 20.8 dB | 20.1 dB | 100 +/- 15 |
| 125 MHz | 21.0 dB/100m | 33.8 dB | 30.8 dB | 12.8 dB | 9.8 dB | 21.9 dB | 18.9 dB | 19.4 dB | 100 +/- 15 |
| 155 MHz | 23.4 dB/100m | 32.4 dB | 29.4 dB | 9.0 dB | 6.0 dB | 20.0 dB | 17.0 dB | 18.8 dB | 100 +/- 22 |
| 175 MHz | 24.9 dB/100m | 31.7 dB | 28.7 dB | 6.8 dB | 3.8 dB | 18.9 dB | 15.9 dB | 18.4 dB | 100 +/- 22 |
| 200 MHz | 26.6 dB/100m | 30.8 dB | 27.8 dB | 4.1 dB | 1.1 dB | 17.8 dB | 14.8 dB | 18.0 dB | 100 +/- 22 |
| 250 MHz | 29.8 dB/100m | 29.3 dB | 26.3 dB | | | 15.8 dB | 12.8 dB | 17.3 dB | 100 +/- 22 |
| 300 MHz | 32.7 dB/100m | 28.1 dB | 25.1 dB | | | 14.3 dB | 11.3 dB | 16.8 dB | 100 +/- 22 |
| 400 MHz | 35.4 dB/100m | 27.1 dB | 24.1 dB | | | 12.9 dB | 9.9 dB | 16.3 dB | 100 +/- 22 |
| 450 MHz | 37.9 dB/100m | 26.3 dB | 23.3 dB | | | 11.8 dB | 8.8 dB | 15.9 dB | 100 +/- 32 |
| 500 MHz | 42.5 dB/100m | 24.8 dB | 21.8 dB | | | 9.8 dB | 6.8 dB | 15.2 dB | 100 +/- 32 |

Voltage

| UL Description | UL Voltage Rating |
|----------------|-------------------|
| CMP | 300 V |

Temperature Range

| | |
|--------------------------|----------------|
| Installation Temp Range: | 0°C To +75°C |
| UL Temp Rating: | 90°C |
| Storage Temp Range: | -20°C to +75°C |
| Operating Temp Range: | -20°C to +75°C |

Mechanical Characteristics

| | |
|--------------------------------------|------------------------------|
| Cold Bend Test: | -20°C Compliance per UL 1581 |
| Bulk Cable Weight: | 36 lbs/1000ft |
| Max. Pull Tension: | 45 lbs |
| Min Bend Radius During Installation: | 2.7 in |
| Min Bend Radius/Minor Axis: | 1.0 in |

Standards

| | |
|---------------|-------------|
| NEC Articles: | Article 800 |
|---------------|-------------|

| | |
|-----------------------|---|
| NEC/(UL) Compliance: | CMP |
| CEC/C(UL) Compliance: | CMP |
| IEC Compliance: | 11801 ed 2.2 (2011) Class D |
| IEEE Compliance: | POE per 802.3af & POE+ 802.3at-2009 |
| Other Compliance: | C(UL)US CMP 90C OR (UL) CMR-LP (0.6A) OR CL3R-LP (0.6A) OR POH, HDBaseT Recommended Cable |

Applicable Environmental and Other Programs

| | |
|--|-----------------|
| Environmental Space: | Indoor - Plenum |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | Yes |
| EU CE Mark: | Yes |
| EU REACH SVHC Compliance (yyyy-mm-dd): | 2017-07-10 |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01 |
| MII Order #39 (China RoHS): | Yes |

Suitability

| | |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

Flammability, LSOH, Toxicity Testing

| | |
|--------------------|----------|
| UL Flammability: | NFPA 262 |
| CSA Flammability: | FT6 |
| UL voltage rating: | 300 V |

Plenum/Non-Plenum

| | |
|---------------|-----|
| Plenum (Y/N): | Yes |
|---------------|-----|

Part Number

| | |
|--------------------|-------|
| Non-Plenum Number: | 2183R |
|--------------------|-------|

Variants

| Item # | Color | Putup Type | Length | UPC |
|----------------|-------|--------------|----------|--------------|
| 2183P 010A250 | Black | Reel-in-Box | 250 ft | 612825392958 |
| 2183P 0101000 | Black | Reel | 1,000 ft | 612825391678 |
| 2183P 010A1000 | Black | Reel-in-Box | 1,000 ft | 612825391708 |
| 2183P 010Z1000 | Black | ReelTuff Box | 1,000 ft | 612825433231 |
| 2183P D15A1000 | Blue | Reel-in-Box | 1,000 ft | 612825391685 |
| 2183P D15Z1000 | Blue | ReelTuff Box | 1,000 ft | 612825433286 |
| 2183P 009A1000 | White | Reel-in-Box | 1,000 ft | 612825391692 |
| 2183P 009Z1000 | White | ReelTuff Box | 1,000 ft | 612825433187 |

Product Notes

| | |
|--------|--|
| Notes: | Values Above 100 MHz are for Engineering Information Only. Print Includes Descending Footage Markings. |
|--------|--|

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.251 Revision Date: 09-30-2020 |
|----------------------|--|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

