



**Product:** [1801BD](#)

Audio Snake Cable, 2 Pair 24 AWG, TC, Individually Shielded, CMP

## Product Description

Digital Audio Snake Cable, Plenum-CMP, 2-24 AWG tinned copper pairs, foam FEP insulation, Flamarrest® jacket, Parallel construction

## Technical Specifications

### Product Overview

Suitable Applications:	Recording Studio, Radio Broadcast, Sports Stadium, Nurse Call
------------------------	---

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
24	7x32	TC - Tinned Copper	0.024 in	2

Conductor Count:	4
------------------	---

#### Insulation

Material	Material Trade Name	Nominal Diameter
FEP - Fluorinated Ethylene Propylene (Foam)	Teflon®	0.066 in

#### Color Chart

Number	Color
1	Red & Black
2	White & Blue

#### Inner Shield Material

Type	Material	Material Trade Name	Drainwire Material	Drainwire AWG
Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	TC - Tinned Copper	24

#### Outer Shield Material

Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Bi-Laminate (Alum+Poly)	100%	TC - Tinned Copper	24	7x32

#### Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.165 x 0.345 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
23.7 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
12 pF/ft	26 pF/ft

#### Inductance

<b>Nominal Inductance</b>
0.18 $\mu$ H/ft

**Impedance**

<b>Nominal Characteristic Impedance</b>
110 Ohm

**High Frequency (Nominal/Typical)**

<b>Nom. Insertion Loss</b>
0.82 dB/100ft
1.01 dB/100ft
1.02 dB/100ft
1.08 dB/100ft
1.15 dB/100ft
1.16 dB/100ft
1.23 dB/100ft
1.34 dB/100ft
1.38 dB/100ft
1.58 dB/100ft
1.79 dB/100ft
1.85 dB/100ft
2.05 dB/100ft
2.34 dB/100ft
2.43 dB/100ft
3.33 dB/100ft

**High Freq**

<b>Frequency [MHz]</b>
0.384 MHz
0.7056 MHz
0.768 MHz
1.024 MHz
1.4112 MHz
1.536 MHz
2.048 MHz
2.8224 MHz
3.072 MHz
4.096 MHz
5.6448 MHz
6.144 MHz
8.192 MHz
11.2896 MHz
12.288 MHz
24.576 MHz

**Current**

<b>Max. Recommended Current [A]</b>
2.9 Amps per Conductor at 25°C

**Voltage**

<b>UL Voltage Rating</b>
300 V RMS

**Temperature Range**

Operating Temp Range:	-20°C To +60°C
-----------------------	----------------

**Mechanical Characteristics**

UV Resistance:	No
Bulk Cable Weight:	26 lbs/1000ft
Max. Pull Tension:	33 lbs
Min Bend Radius/Minor Axis:	1.75 in

## Standards

NEC/(UL) Compliance:	CMP
CEC/C(UL) Compliance:	CMP
Other Compliance:	AES/EBU

## Applicable Environmental and Other Programs

Environmental Space:	Indoor - Plenum
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

## Flammability, LSOH, Toxicity Testing

C(UL) Flammability:	FT6
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

## Part Number

### Variants

Item #	Color	Putup Type	Length	UPC
1801BD 8771000	Natural	Reel	1,000 ft	612825122982
1801BD Z4B1000	Violet Z4B	Reel	1,000 ft	612825122975

## Product Notes

Notes:	Teflon® is a registered trademark of Chemours and is used under license by Belden, Inc.
--------	---

## History

Update and Revision:	Revision Number: 0.287 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.