



Product: <u>YE00820</u> ☑

KNX, 2PR 0.8mm Sol BC, PVC ins,OS, PVC jkt, Eca

Product Description

KNX, 2 Pair AWG Bare Copper - Solid, PVC insulation, Foil(s) or Copper Tape(s) shielding, PVC jacket , CPR Eca

Technical Specifications

Product Overview

| Suitable Applications: | | | KNX, | KNX, EIB cable for building management | | | | |
|------------------------------------|----------|---------------|------------------|--|---|--|--|--|
| Physical Characteristics (Overall) | | | | | | | | |
| | | | | | | | | |
| Conductor | | | | | 1 | | | |
| Stranding | Material | Cross Section | Nominal Diameter | No. of Conductors | | | | |

| Stranding | Material | Cross Section | Nominal Dian | meter | No. of Conductors |
|------------------------|------------------|----------------------|--------------|-------|-------------------|
| Solid | BC - Bare Copper | 0.5 mm ² | 0.8 mm | | 4 |
| Conductor Count: | | | 4 | | |
| Total Number of Pairs: | | | 2 | | |

Insulation

| Material | Nominal Diameter | Diameter +/- Tolerance | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|------------------------|
| PVC - Polyvinyl Chloride | 1.4 mm | 0.05 mm | 0.3 mm |

Color Chart

 Number
 Color

 Quad 1
 White & Red & Yellow & Black

Outer Shield Material

| Туре | Material | Material Trade Name | Coverage [%] | Thickness of Foil | Drainwire Material | Drainwire Diameter |
|------|----------------------------|---------------------|--------------|-------------------|--------------------|--------------------|
| Tape | Bi-Laminate (Alum+Poly) | Beldfoil® | 100% | 9 µm | TC - Tinned Copper | 0.4 mm |

Outer Jacket Material

| Material | Nominal Diameter | Diameter - Tolerance | Nominal Wall Thickness |
|--------------------------|------------------|----------------------|------------------------|
| PVC - Polyvinyl Chloride | 6.1 mm | 0.3 mm | 1.2 mm |

Construction and Dimensions

Cabling

Description
1 quad covered with a polyester foil

Electrical Characteristics

Conductor DCR

Max. Conductor DCR 37.5 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor

50 pF/m

Temperature Range

| Storage Temp Range: | -30°C to +70°C |
|-----------------------|----------------|
| Operating Temp Range: | -20°C To +70°C |

Mechanical Characteristics

| Min Bend Radius During Installation: | 30.5 mm |
|--------------------------------------|---------------------|
| Standards | |
| CPR Euroclass: | Еса |
| Other Compliance: | KNX REG 109/7253/05 |

Applicable Environmental and Other Programs

| Environmental Space: | Indoor - Euroclass Eca |
|---------------------------------------|------------------------|
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-01-01 |

Flammability, LS0H, Toxicity Testing

IEC Flammability:

IEC 60332-1-2

Part Number

Variants

| Item # | Color | Putup Type | Length | EAN |
|----------------|-------|------------|---------|---------------|
| YE00820.00100 | Green | Reel | 100 m | 8719605112606 |
| YE00820=00100 | Green | Reel | 100 m | 8719605161291 |
| YE00820=K0100 | Green | Reel | 100 m | 8719605161253 |
| YE00820.00500 | Green | Reel | 500 m | 8719605112637 |
| YE00820=00500 | Green | Reel | 500 m | 8719605161321 |
| YE00820=K0500 | Green | Reel | 500 m | 8719605161284 |
| YE00820.001000 | Green | Reel | 1,000 m | 8719605112613 |
| YE00820=001000 | Green | Reel | 1,000 m | 8719605161307 |
| YE00820=K01000 | Green | Reel | 1,000 m | 8719605161260 |
| YE00820.001525 | Green | Reel | 1,525 m | 8719605112620 |
| YE00820=001525 | Green | Reel | 1,525 m | 8719605161314 |
| YE00820=K01525 | Green | Reel | 1,525 m | 8719605161277 |

History

Update and Revision:

Revision Number: 0.139 Revision Date: 12-18-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.