



Product: [3072Z](#)

Blue Hose®, 1 Pr #18 Str TC, PP Ins, OS+TC Brd, LSZH-TS Jkt, 600V TC-ER-ST1

Product Description

Blue Hose® for Data Highway Plus, 1 Pair 18AWG (7x26) Tinned Copper, Polypropylene Insulation, Overall Beldfoil®+Tinned Copper Braid(55%) Shield, LSZH Thermoset Outer Jacket, 600V TC-ER-ST1

Technical Specifications

Suitable Applications: shipboard, harsh environment, IIoT, factory or process automation, video, audio, data communication, etc.

Conductor

| Element | Number of Element | AWG | Stranding | Material |
|---------|-------------------|-----|-----------|--------------------|
| Pair(s) | 1 | 18 | 7x26 | TC - Tinned Copper |

Insulation

| Element | Material | Thickness | Color Code | Notes |
|---------|--------------------|-----------|--------------|-----------------|
| Pair(s) | PP - Polypropylene | 0.025 in | Blue & White | Flame Retardant |

Outer Shield Material

| Shield Type | Material | Coverage | Drainwire Type |
|--------------|--|------------|------------------|
| Tape + Braid | Bi-Laminate (Alum+Poly) + Tinned Copper (TC) | 100% + 55% | 20 AWG (7x28) TC |

Outer Jacket Material

| Material | Thickness | Nom. Diameter |
|--|-----------|---------------|
| LSZH - Low Smoke Zero Halogen (Flame Retardant, Thermoset) | 0.100 in | 0.480 in |

Cable Diameter (Nominal): 0.480 in

Electricals

| Element | Characteristic Impedence | Nom. Velocity of Prop. |
|---------|--------------------------|------------------------|
| Pair(s) | 78 Ohm | 65% |

High Frequency (Nominal/Typical)

| Element |
|---------|
| Pair(s) |

Voltage

| UL Voltage Rating | Non-UL Voltage Rating |
|--|-----------------------|
| 600 V (TC-ER-ST1), 300 V (CMG-ST1, PLTC-ST1) | 150 V (ITC-ST1) |

Temperature

| UL Rating |
|-----------|
| 75°C Dry |

| | |
|----------------------------|--|
| Environmental Suitability: | Burial |
| NEC / UL Compliance: | Article 336, Article 725, Article 727, Article 800, CMG-ST1, TC-ER-ST1, PLTC-ST1,ITC-ST1 |
| CEC / C(UL) Compliance: | CMG |
| CPR Euroclass: | Fca |
| Update and Revision: | Revision Number: 0.122 Revision Date: 09-30-2020 |

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.