



Product: [70082CH](#) 

COAX RG6/U LSZH-C HDTV PRECISION VIDEO

Product Description

COAX [1.0/4.6] RG6/U LSZH-C HDTV EASY CONNECT PRO

Technical Specifications

Product Overview

Suitable Applications:	Low loss HDTV/SDI Digital coax used in analog and digital video circuits and high quality applications; The cable is UV-resistant and suitable for indoor and outdoor use; Use of 1080p/50 applications
------------------------	---

Physical Characteristics (Overall)

Conductor					
AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
18	Solid	BC - Bare Copper	1.02 mm	0.03 mm	1
Conductor Count:			1		

Insulation			
Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene (Foam)	4.57 mm	0.15 mm

Outer Shield Material						
Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Coverage +/- Tolerance
Tape	1	Tri-Laminate (Alum+Poly+Alum)	100%	2 mm		
Braid	2	Tinned Copper (TC)	80%		5.3 mm	5%

Outer Jacket Material		
Material	Nominal Diameter	Diameter +/- Tolerance
LSZH - Low Smoke Zero Halogen (Flame Retardant)	6.96 mm	0.2 mm

Construction and Dimensions

Min Elongation at Breakof Jacket:	125 %
Min Tensile Strength of Jacket:	9 MPa

Electrical Characteristics

Conductor DCR	
Max. Conductor DCR	Max. Shield DCR
21 Ohm/km	9.7 Ohm/km

Capacitance	
Nom. Capacitance	Capacitance Tolerance
53 pF/m	2 pF/m

Impedance	
Nominal Characteristic Impedance	Nominal Characteristic Tolerance
75 Ohm	3 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.8 dB/100m
10 MHz	2.4 dB/100m
71.5 MHz	5.6 dB/100m
135 MHz	7.4 dB/100m
270 MHz	10.4 dB/100m
360 MHz	12.1 dB/100m
540 MHz	15 dB/100m
720 MHz	17.5 dB/100m
750 MHz	17.9 dB/100m
1000 MHz	21 dB/100m
1500 MHz	26 dB/100m
2250 MHz	32 dB/100m
3000 MHz	38 dB/100m
4500 MHz	48 dB/100m

Table Notes:	Max. attenuation 10% higher
--------------	-----------------------------

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
407 ns/ft	82%

High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 1600 MHz	23 dB
1600 - 4500 MHz	21 dB

Voltage

Voltage Test Dielectric
2.0 kV DC

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-30°C To +70°C
Operating Temp Range:	-30°C To +70°C

Mechanical Characteristics

Max. Pull Tension:	300 N
Min Bend Radius (W/o Pulling Strength):	70 mm

Standards

CENELEC Compliance:	EN 50117-1 and EN 50290-2-20
RG Type:	6/U Type
Other Compliance:	SDTV/HDTV

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU RoHS Compliance Date (yyyy-mm-dd):	2013-10-21

Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-3-24 (Cat. C)
IEC 60754-1 (EN50267-1)- Halogen Amount:	Zero
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Min. pH:	4.3
IEC 61034-2 (EN 61034-2) (VDE 0482-1034) - Smoke Density Min. Transmittance:	60%

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
70082CH.11500	Cream	Reel	500 m	8719605011350
70082CH.00100	Green	Reel	100 m	8719605011305
70082CH.00500	Green	Reel	500 m	8719605011312
70082CH.01500	Purple	Reel	500 m	8719605011329
70082CH.03100	Yellow	Reel	100 m	8719605011336
70082CH.03500	Yellow	Reel	500 m	8719605011343

History

Update and Revision:	Revision Number: 0.186 Revision Date: 12-17-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.