




Product: [3079E](#) 

Profibus, 1 Pr #22 Str BC, PE Ins, OS+TC Brd, PVC Jkt, PLTC CMG Profibus DP

 [Request Sample](#)

Product Description

Profibus, 1 Pair 22AWG (7x30) Bare Copper, PE Insulation, Overall Beldfoil®+Tinned Copper Braid(65%) Shield, PVC Outer Jacket, PLTC CMG SUN RES Profibus DP

Technical Specifications

Suitable Applications: harsh environment, outdoors, data transmission applications such as Profibus DP or PA, Instrumentation and computer cable, etc. exposure to temperature extremes, humidity/moisture, dust, and oil.

Conductor

Element	Number of Element	AWG	Stranding	Material
Pair(s)	1	22	7x30	BC - Bare Copper

Insulation

Element	Material	Thickness	Color Code	Notes
Pair(s)	PE - Polyethylene (Foam)	0.035 in	Red & Green	Flame Retardant, Foam w/ skin

Outer Shield Material

Shield Type	Material	Coverage
Tape + Braid	Bi-Laminate (Alum+Poly) + Tinned Copper (TC)	100% + 65%

Outer Jacket Material

Material	Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.043 in	0.314 in

Cable Diameter (Nominal): 0.314 in

Electricals

Element	Nom. Conductor DCR	Characteristic Impedence	Nom. Velocity of Prop.	Max. Current
Pair(s)	16 Ohm/1000ft	150 Ohm	78%	2.3 Amps per Conductor

Nom Outer Shield DCR: 3.9 Ohm/1000ft

High Frequency (Nominal/Typical)

Element
Pair(s)

High Freq

Max. Insertion Loss (Attenuation)
0.51 dB/100m
1.57 dB/100m
4.8 dB/100m

Voltage

UL Voltage Rating
300 V (CMG, PLTC)

Temperature

UL Rating	Operating
60°C	-30°C to +75°C

Bend Radius

Stationary Min.	Installation Min.
3.2 in	2.5 in

Max. Pull Tension:	50 lbs
Bulk Cable Weight:	39 lbs/1000ft
Environmental Suitability:	Indoor, Sunlight Resistance
Flammability / Fire Resistance:	UL1685 FT4 Loading, FT4, 1202, IEC 60332-1-2
NEC / UL Compliance:	Article 725, Article 800, CMG, PLTC
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
Update and Revision:	Revision Number: 0.360 Revision Date: 09-30-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.