

Product: [7783AFP](#) 

VIDEO TRIAX 8 STRANDED PUR



Product Description

VIDEO TRIAX 8 STRANDED PUR

Technical Specifications

Product Overview

Suitable Applications:	Triaxial camera cable used to interconnect video cameras to related equipment.; Triax cable contain 2 isolated shields and a solid or stranded center conductor.; Isolated shields allow the triax cable to provide multiple functions over 1 cable through multiplexing techniques
------------------------	---

Physical Characteristics (Overall)

Conductor				
AWG	Stranding	Material	Nominal Diameter	No. of Coax
18	Stranded	SC - Silvered Copper	0.99 mm	1
Conductor Count: 1				

Insulation		
Material	Nominal Diameter	Diameter +/- Tolerance
PE - Polyethylene (Foam)	4.52 mm	0.2 mm

Inner Shield Material			
Type	Material	Nominal Diameter	Min. Coverage [%]
Braid	Silvered Copper (SC)	5.1 mm	80%

Inner Jacket Material		
Material	Nominal Diameter	Diameter +/- Tolerance
PE - Polyethylene	6.6 mm	0.2 mm

Outer Shield Material			
Type	Material	Nominal Diameter	Min. Coverage [%]
Braid	Bare Copper (BC)	7.2 mm	80%

Outer Jacket Material		
Material	Nominal Diameter	Diameter +/- Tolerance
PUR - Polyurethane	8.4 mm	0.2 mm

Electrical Characteristics

Conductor DCR		
Nominal Conductor DCR	Nominal Inner Shield DCR	Nominal Outer Shield DCR
32 Ohm/km	14 Ohm/km	9 Ohm/km

Capacitance	
Nom. Capacitance Conductor to Shield	
52 pF/m	

Inductance	

Nominal Inductance
0.4 µH/m

Impedance

Nominal Characteristic Impedance
75 Ohm

Return Loss (RL)

Frequency [MHz]	Min. Structural Return Loss (SRL)
5-850	21 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.6 dB/100m
10 MHz	2.2 dB/100m
20 MHz	3.2 dB/100m
40 MHz	4.6 dB/100m
50 MHz	5.1 dB/100m
60 MHz	5.6 dB/100m
100 MHz	7.5 dB/100m
300 MHz	13.8 dB/100m

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
410 ns/100m	83%

Screening

Frequency [MHz]	Min. Screening Attenuation
30-1000 MHz	75

Temperature Range

Installation Temp Range:	-5°C To +70°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

Mechanical Characteristics

Max. Pull Tension:	250 N
Min Bend Radius (W/o Pulling Strength):	80 mm

Standards

Series Type:	Triax 8/11/14
--------------	---------------

Applicable Environmental and Other Programs

Environmental Space:	Indoor/Outdoor
EU RoHS Compliance Date (yyyy-mm-dd):	2014-04-11

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
7783AFP.01500	Red	Reel	500 m	8719605014139

History

Update and Revision:	Revision Number: 0.141 Revision Date: 09-30-2020
----------------------	--

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.