



Product: [7783E](#) 

VIDEO TRIAX 8 PVC



Product Description

VIDEO TRIAX 8 PVC

Technical Specifications

Product Overview

Suitable Applications:	Triaxial camera cable
------------------------	-----------------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
18	Solid	BC - Bare Copper	1.02 mm	1

Conductor Count:	1
------------------	---

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene (Foam)	4.57 mm	0.2 mm

Inner Shield Material

Type	Material	Coverage [%]	Nominal Diameter
Braid	Bare Copper (BC)	80%	5.1 mm

Inner Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PE - Polyethylene	6.6 mm	0.2 mm

Outer Shield Material

Type	Material	Nominal Diameter	Min. Coverage [%]
Braid	Bare Copper (BC)	7.2 mm	80%

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	8.4 mm	0.2 mm

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Inner Shield DCR	Nominal Outer Shield DCR
22 Ohm/km	13 Ohm/km	8.5 Ohm/km

Capacitance

Nom. Capacitance Conductor to Shield
52 pF/m

Inductance

Nominal Inductance

0.4 µH/m

Impedance

Nominal Characteristic Impedance

75 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.7 dB/100m
5 MHz	1.5 dB/100m
10 MHz	2.2 dB/100m
70 MHz	5.7 dB/100m
100 MHz	6.9 dB/100m
140 MHz	8.2 dB/100m
200 MHz	9.8 dB/100m
300 MHz	12.2 dB/100m
400 MHz	14.2 dB/100m
500 MHz	16 dB/100m
700 MHz	19.1 dB/100m
800 MHz	20.5 dB/100m
1000 MHz	23.2 dB/100m
1500 MHz	29 dB/100m
2000 MHz	34 dB/100m
2400 MHz	37.8 dB/100m

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
410 ns/ft	83%

High Freq

Frequency [MHz]	Min. SRL (Structural Return Loss)
5 - 850 MHz	23 dB

Voltage

Voltage Rating [V]

400 V RMS

Table Notes:	Maximum operating
--------------	-------------------

Temperature Range

Installation Temp Range:	-5°C To +70°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

Mechanical Characteristics

Max. Pull Tension:	250 N
Min Bend Radius (W/o Pulling Strength):	80 mm

Standards

Series Type:	Triax 8/11/14
--------------	---------------

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU RoHS Compliance Date (yyyy-mm-dd):	2016-05-20

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
7783E.02500	Red	Reel	500 m	8719605014153
7783E.021000	Red	Reel	1,000 m	8719605014146

History

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.