



Product: [BE43800](#)

Railtuff ® 5E, 4PR #26 Str BC, PO ins, SF/UTP, LSNH Jkt, EN 45545-2

Product Description

Railtuff ® 5E, 4 Pair AWG 26 Bare Copper - Stranded, Polyolefin (PO, PE, PP) insulation, SF/UTP - Overall Braid + Foil shielding, Crosslinked e-beam LSZH / FRNC jacket , EN 45545-2 HL1 - 3

Technical Specifications

Product Overview

Suitable Applications:	For use in railway applications such as rolling stock, buses or other vehicles, cable meets the requirements of the relevant part of international railway standards like DIN 5510-2, EN 50153, EN 50155, EN 50305 and EN 45545-2
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Construction n x D	No. of Pairs
26	Stranded	BC - Bare Copper	19x0.10 mm	4

Conductor Count:	8
Total Number of Pairs:	4

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance
PO - Polyolefin	1 mm	0.05 mm

Bonded-Pair:	No
--------------	----

Color Chart

Number	Color
Pair 1	White/Blue & Blue
Pair 2	White/Orange & Orange
Pair 3	White/Green & Green
Pair 4	White/Brown & Brown

Outer Shield Material

Type	Material	Min. Coverage [%]
Tape	Bi-Laminate (Alum+Poly)	
Braid	Tinned Copper (TC)	85%

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance	Min. Wall Thickness
LSZH - Low Smoke Zero Halogen (Flame Retardant, Thermoset)	6.7 mm	0.2 mm	0.9 mm

Table Notes:	e-Beamed to Cross-link
--------------	------------------------

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
14.5 Ohm/km	4 %	2 %

Capacitance

Max. Capacitance Unbalance	Max. Mutual Capacitance
1.6 pF/m	56 pF/m

Delay

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
40 ns/100m	60%

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	3.2 dB/100m	65.3 dB	62.3 dB	62.1 dB	59.1 dB	64 dB	61 dB	20 dB	40 dB	35 dB
4 MHz	6 dB/100m	56.3 dB	53.3 dB	50.3 dB	47.3 dB	52 dB	49 dB	23 dB	34 dB	23 dB
10 MHz	9.5 dB/100m	50.3 dB	47.3 dB	40.8 dB	37.8 dB	44 dB	41 dB	25 dB	30 dB	15 dB
16 MHz	12.1 dB/100m	47.2 dB	44.2 dB	35.2 dB	32.2 dB	39.9 dB	36.9 dB	25 dB	28 dB	10.9 dB
20 MHz	13.5 dB/100m	45.8 dB	42.8 dB	32.2 dB	29.2 dB	38 dB	35 dB	25 dB	27 dB	9 dB
31.25 MHz	17.1 dB/100m	42.9 dB	39.9 dB	25.8 dB	22.8 dB	34.1 dB	31.5 dB	23.6 dB	25.1 dB	5.5 dB
62.5 MHz	24.8 dB/100m	38.4 dB	35.4 dB	13.6 dB	10.6 dB	28.1 dB	25.1 dB	21.5 dB	22 dB	
100 MHz	33 dB/100m	35.3 dB	32.3 dB	3.3 dB	0.3 dB	24 dB	21 dB	20.1 dB	20 dB	

Table Notes:	According ISO/IEC 11801 Cat. 5e and ISO/IEC 61156-5
General Electrical Parameters Notes:	According ISO/IEC 11801 Cat. 5e and ISO/IEC 61156-5
Coupling Attenuation Class:	Type I
Segregation class according EN50174-2:	d

Transfer Impedance

Frequency [MHz]	Description	Transfer Impedance
1 Mhz	Grade 1	Max. 10 mOhm/m
10 Mhz		Max. 10 mOhm/m
30 Mhz		Max. 30 mOhm/m
100 Mhz		100 mOhm/m

Voltage

Voltage Rating [V]
300 V

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C To +90°C
Operating Temp Range:	-40°C To +90°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-2-1
Min Bend Radius (W/o Pulling Strength):	67 mm
Min Setting Radius:	33.5 mm

Standards

CENELEC Compliance:	EN 45545-2 Hazard Level HL1-HL3
Data Category:	Category 5e
Other Compliance:	EN 50306 par 4.8 + 4.9 + 4.10 (1.5 kV/1min); Toxicity index to NF X70-100 CITc Max. 0.7, EN 45545-2 (Class R14 HL 3)

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01

Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2 and IEC 60332-3-25
Fire Resistance (Time to Failure) Compliance:	DIN 5510-2 protection level 1 to 4
Other Flammability:	EN45545-2:2013 HL1 to HL 3 ; EN 50305 9.1.1 ; UN ECE-R118.02
IEC 60754-1 (EN50267-1)- Halogen Amount:	Zero
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Min. pH:	4.3

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
BE43800.00305	Black	Reel	305 m	8719605026552
BE43800.00500	Black	Reel	500 m	8719605026569
BE43800.001000	Black	Reel	1,000 m	8719605026545

History

Update and Revision:	Revision Number: 0.248 Revision Date: 12-18-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.