


Product: [H126D03](#) 

## COAX H126 DUOBONDPLUS LSZH



### Product Description

COAX [1.0/4.6] H126 DUOBONDPLUS LSZH

### Technical Specifications

#### Product Overview

Suitable Applications:	Coaxial cables used in cabled distribution networks designed according the European Standard EN 50117-2-1 and EN 50117-2-4; Operating at frequencies between 5 MHz and 3000 MHz
------------------------	---

#### Physical Characteristics (Overall)

##### Conductor

AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
18	Solid	BC - Bare Copper	1 mm	0.03 mm	1

Conductor Count:	1
------------------	---

##### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene (Foam)	4.57 mm	0.15 mm

##### Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Tri-Laminate (Alum+Poly+Alum)	100%	1 mm			
Braid	2	Tinned Copper (TC)	45%		5.4 mm	0.2 mm	5%
Tape	3	Bi-Laminate (Alum+Poly)	100%	1 mm			

##### Outer Jacket Material

Material	Nominal Diameter	Diameter + Tolerance	Diameter - Tolerance
LSZH - Low Smoke Zero Halogen (Flame Retardant)	6.9 mm	0.6 mm	0.2 mm

Table Notes:	According to European Standard EN 50290-2-20
--------------	--

#### Construction and Dimensions

Min Elongation at Breakof Jacket:	125 %
Min Tensile Strength of Jacket:	9 MPa

#### Electrical Characteristics

##### Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
23 Ohm/km	37 Ohm/1000ft	14 Ohm/km

##### Capacitance

Nom. Capacitance	Capacitance Tolerance
54 pF/m	2 pF/m

##### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
----------------------------------	----------------------------------	-------------------------

75 Ohm	3 Ohm	Min. 40 dB
--------	-------	------------

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	1.8 dB/100m
50 MHz	4.7 dB/100m
100 MHz	6.5 dB/100m
230 MHz	9.8 dB/100m
400 MHz	13 dB/100m
800 MHz	18.7 dB/100m
862 MHz	19.5 dB/100m
1000 MHz	21.1 dB/100m
1350 MHz	24.9 dB/100m
1750 MHz	28.8 dB/100m
2150 MHz	32.3 dB/100m
2400 MHz	34.4 dB/100m
3000 MHz	39.2 dB/100m

Table Notes: Max. attenuation 10% higher

#### Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
82%	2%

#### High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 470 MHz	20 dB
470 - 1000 MHz	18 dB
1000 - 2000 MHz	16 dB
2000 - 3000 MHz	15 dB

Table Notes: In each frequency band, 3 peak values up to 4 dB lower are allowed

#### Screening

Frequency [MHz]	Min. Screening Attenuation After Flexing
30 - 1000 MHz	100 dB
1000 - 2000 MHz	100 dB
2000 - 3000 MHz	100 dB

Screening Class: A

#### Transfer Impedance

Transfer Impedance
Max. 4.5 mOhm/m

#### Voltage

Voltage Test Dielectric
2.0 kV DC

#### Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-30°C To +70°C
Operating Temp Range:	-30°C To +70°C

#### Mechanical Characteristics

Min Bend Radius (W/o Pulling Strength):	65 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	7.8-78 N at 25 mm N

#### Standards

CPR Euroclass:	Dca-s1,d1,a1
CENELEC Compliance:	EN 50117-2-1, EN 50117-2-4 and EN 50117-1
RG Type:	6/U Type

#### Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Dca
EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01

## Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2 and IEC 60332-3-24
LOI of Jacket:	Min. 35 %
IEC 60754-1 (EN50267-1)- Halogen Amount:	Zero
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Min. pH:	4.3

## Part Number

### Variants

Item #	Color	Putup Type	Length	EAN
H126D03.00B100	White	Flat Box	100 m	8719605087478
H126D03.00U250	White	UnReel	250 m	8719605087485
H126D03.00500	White	Reel	500 m	8719605087447
H126D03.005000	White	Reel	5,000 m	8719605087454

## History

Update and Revision:	Revision Number: 0.184 Revision Date: 12-17-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.