


Product: [H124C01](#) 

TRIAX H124 CU LSZH-C



Product Description

TRIAX [1.0/4.4] H124 CU LSZH-C

Technical Specifications

Product Overview

Suitable Applications:	Cable fulfills according standard E4156.1-A3 and E4156.2-A4 of London Underground
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
18	Solid	BC - Bare Copper	1 mm	0.03 mm	1

Conductor Count:	1
------------------	---

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene (Foam)	4.4 mm	0.15 mm

Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Bare Copper (BC)	100%	2 mm			
Braid	2	Bare Copper (BC)	40%		5 mm	0.2 mm	4%

Outer Shield Material 2

Type	Material	Coverage	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Braid	Bare Copper (BC)	60 %	7.5 mm	0.3 mm	5 %

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance	Min. Wall Thickness
LSZH - Low Smoke Zero Halogen (Flame Retardant)	7 mm	0.2 mm	1 mm

Table Notes:	According to European Standard EN 50290-2-20
--------------	--

Outer Jacket Material 2

Material	Color	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
LSZH - Low Smoke Zero Halogen (Flame Retardant)	Black (RAL 9005)	8.8 mm	0.3 mm	0.65 mm

Table Notes:	According to European Standard EN 50290-2-20
--------------	--

Construction and Dimensions

Min Elongation at Breakof Conductors:	15 %
Min Elongation at Breakof Jacket:	125 %
Min Tensile Strength of Jacket:	9 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. Inner Shield DCR	Max. Shield DCR
23 Ohm/km	19 Ohm/km	14 Ohm/km

Capacitance

Capacitance Tolerance	Nom. Capacitance Conductor to Shield
2 pF/m	53 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
75 Ohm	3 Ohm	Min. 40 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	1.3 dB/100m
50 MHz	4.3 dB/100m
100 MHz	6.1 dB/100m
200 MHz	8.8 dB/100m
400 MHz	12.7 dB/100m
600 MHz	15.8 dB/100m
800 MHz	18.5 dB/100m
1000 MHz	20.9 dB/100m
1350 MHz	24.7 dB/100m
1750 MHz	28.6 dB/100m
2150 MHz	32.1 dB/100m
2400 MHz	34.2 dB/100m

Table Notes: Max. attenuation 10% higher

Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
84%	2%

High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 30 MHz	23 dB
30 - 470 MHz	23 dB
470 - 862 MHz	20 dB
862 - 2150 MHz	18 dB

Table Notes: In each frequency band, 3 peak values up to 4 dB lower are allowed

Screening

Frequency [MHz]	Min. Screening Attenuation
30 - 1000 MHz	75 dB

Voltage

Voltage Test Dielectric
2.0 kV DC

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-15°C To +70°C
Operating Temp Range:	-15°C To +70°C

Mechanical Characteristics

UV Resistance:	Yes
Bulk Cable Weight:	99 kg/km
Min Bend Radius (W/o Pulling Strength):	90 mm
Crush Resistance:	Max. 1% (load of 700N) N

Standards

GENELEC Compliance:	EN 50117-1
RG Type:	6/U Type
Other Compliance:	E4156.1-A2 and E4156.2-A4 of London Underground

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
H124C01.01500	Black	Reel	500 m	8719605086211
H124C01.00500	Gray	Reel	500 m	8719605086198

History

Update and Revision:	Revision Number: 0.185 Revision Date: 12-17-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.